

Cable gland - G-INB-M40-M68N-NEPDS-S - 1415185

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Nickel-plated brass, Application: Standard, External cable diameter 16 mm ... 28 mm, Shielding: No, Connecting thread: M40, Color: silver

The figure shows version G-INB-M25-S68N-NEPDS-S



Key Commercial Data

Packing unit	1 pc
Custom tariff number	74199990
Country of origin	Germany

Technical data

Dimensions

Length	184 mm
Length without connecting thread	176 mm
Connecting thread diameter	40 mm
Wrench size, union nut	46 mm
Wrench size, support	46 mm
Hexagon angular dimension GRP	51 mm
Length of the connecting thread	8 mm
External cable diameter	16 mm ... 28 mm

Ambient conditions

Degree of protection	IP68 (5 bar / 0.5 h)
	IP69K
Ambient temperature (operation)	-40 °C ... 100 °C (dynamic)

General

Cable gland material	Nickel-plated brass
Seal material	EPDM

Cable gland - G-INB-M40-M68N-NEPDS-S - 1415185

Technical data

General

Shielded	No
Thread type on connection side	M40
Color	silver

Classifications

eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109

ETIM

ETIM 5.0	EC000441
----------	----------

Approvals

Approvals


Approvals


UL Recognized / cUL Recognized / GOST-R / cULus Recognized

Ex Approvals

Approvals submitted


Approval details

UL Recognized 

cUL Recognized 
--

Cable gland - G-INB-M40-M68N-NEPDS-S - 1415185

Approvals



Drawings

Dimensional drawing

