## **HellermannTyton**

## **Specification Sheet**

Part Number: 596-73833



White polyester is glossy, allowing for the highest resolution and print contrast.

The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

The printable surface is highly resistant to chemicals and solvents and can withstand long-term UV exposure.

Thermal Transfer Labels, High-Bond Adhesive, 2.0" x 1.0", Polyester, White, 3000/roll

Article Number 596-73833

Type PCP2X1

Color White (WH)

Quantity Per roll

Product Description For the ultimate in chemical and solvent resistance and long term

outdoor durability, the 840 white polyester offers the most aggressive performance features of any other polyester label material. With an initial outdoor life of 7 years, the labels have been tested far beyond the published limits and the acrylic adhesive bonds well to powder coat painted surfaces as well as baked enamel and slightly textured

substrates.

Short Description Thermal Transfer Labels, High-Bond Adhesive, 2.0" x 1.0", Polyester,

White, 3000/roll

	_	
Global	Dort	Nama
Giobai	ган	manne

PCP2X1-840W-WH

Width W (Imperial)

2.0

Width W (Metric)

50.8

Thickness T (Metric)

64.0

Height H (Imperial)

1.0

Height H (Metric)

25.4

Width of Liner (Metric)

122.9

Width of Liner (Imperial)

2.2

Material

Type 840W, Polyester, white (840W)

**Material Shortcut** 

840W

Adhesive

High Bond Acrylic

Halogen Free

No

UV Resistant (Yes/No)

No

Adhesive Operating Temperature

-40°F to +302°F (-40°C to +150°C)

**Operating Temperature** 

-40°F to +300°F (-40°C to +149°C)

Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	CSA 66956
UL Recognized (US)	Yes
Package Quantity (Imperial)	3000
Package Quantity (Metric)	3000
Customs Number	3919102055
Labels per Column	1
Labels per Row	1

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions