

## Han3A RJ45 Hybrid power jack SMD T&R



Image is for illustration purposes only. Please refer to product description.

Part number	09 45 525 0041
Specification	Han3A RJ45 Hybrid power jack SMD T&R
HARTING eCatalogue	<a href="https://b2b.harting.com/09455250041">https://b2b.harting.com/09455250041</a>

### Identification

Category	Connectors
Series	RJ45 Hybrid
Element	Power module
Specification	for direct device integration

### Version

Termination method	Reflow soldering termination (SMT)
Size	Han <sup>®</sup> 3 A
Shielding	Fully shielded, 360° shielding contact
Number of contacts	0
Pack contents	100 pieces on reel

### Technical characteristics

Conductor cross-section	1.5 mm <sup>2</sup>
Limiting temperature	-40 ... +70 °C
Mating cycles	≥500

### Material properties

RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained



**Pushing Performance**  
Since 1945

## Material properties

REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel Naphthalene

## Specifications and approvals

Approvals	DNV GL
PROFINET	Yes

## Commercial data

Packaging size	100
Net weight	7.39 g
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140060999
eCl@ss	27440205 Contact insert for industrial connectors