

**PZ 6 ROTO****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Crimping tools for wire end ferrules, with and without plastic collars**

- Ratchet guarantees precise crimping
- Release option in the event of incorrect operation

**General ordering data**

|            |  |
|------------|--|
| Version    | Pressing tool, Crimping tool for wire-end ferrules, 0.14mm <sup>2</sup> , 6mm <sup>2</sup> , Trapezoidal crimp |
| Order No.  | <a href="#">9014350000</a>   |
| Type       | PZ 6 ROTO  |
| GTIN (EAN) | 4008 190406615   |
| Qty.       | 1 pc(s).   |

Creation date November 27, 2020 3:39:00 PM CET

Catalogue status 20.11.2020 / We reserve the right to make technical changes.

**PZ 6 ROTO****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |          |                |            |
|------------|----------|----------------|------------|
| Net weight | 427.28 g | Weight         | 428 g      |
| Width      | 200 mm   | Width (inches) | 7.874 inch |

**Environmental Product Compliance**

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

**Technical data**

|                        |                  |         |   |
|------------------------|------------------|---------|---|
| Description of article | (1)Crimping tool | Version | Mechanical, without interchangeable inserts |
|------------------------|------------------|---------|---|

**Description of contact**

|                                   |  |                                   |                      |
|-----------------------------------|--|-----------------------------------|----------------------|
| Conductor cross-section, max. AWG | AWG 10   | Conductor cross-section, min. AWG | AWG 26               |
| Crimping range, max.              | 6 mm <sup>2</sup>                              | Crimping range, min.              | 0.14 mm <sup>2</sup> |
| Type of contact                   | Wire-end ferrules with/without plastic collars |                                   |                      |

**tool data crimping**

|                                       |                      |                                       |                   |
|---------------------------------------|----------------------|---------------------------------------|-------------------|
| Crimping type/profile                 | Trapezoidal crimp    | Wire end ferrules cross-section, max. | 6 mm <sup>2</sup> |
| Wire end ferrules cross-section, min. | 0.14 mm <sup>2</sup> |                                       |                   |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000168    | ETIM 7.0    | EC000168    |
| eClass 9.0  | 21-04-38-11 | eClass 9.1  | 21-04-38-11 |
| eClass 10.0 | 21-04-38-11 | eClass 11.0 | 21043811    |

**Approvals**

Approvals

**Downloads**

|                    |                                      |
|--------------------|--------------------------------------|
| Brochure/Catalogue | <a href="#">CAT 6 TOOLS 15/16 EN</a> |
| Engineering Data   | <a href="#">STEP</a>                 |
| Engineering Data   | <a href="#">WSCAD</a>                |
| User Documentation | <a href="#">Manual</a>               |

**PZ 6 ROTO**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

