

# HG 2620 E

**NEW!**

Available October 2016


## Technical Specifications

**Voltage:** 120 VAC / 60Hz  
**Output:** 1750 watts  
**Amps:** 14.6  
**Temperature:** 120 – 1300 °F (50 – 700 °C) (continuously variable)  
**Airflow rate:** 2 – 13 cfm. (continuously variable)  
**Air pressure:** 3,000 Pa  
**Highlights:** Restart protection, LCD display always in view, 4 settings programmable, locable override funktion (LOC), single-hand operation by toggle, magnesium guard sleeve, plug-in heating element, residual heat indicator, fine dust filter, construction use, easily replaceable power cord, ergonomic soft grip handle, optional temperature scanner  
**Power cord:** Industrial grade rubber  
**Motor:** Brushless motor  
**Heating element:** Ceramic heating element  
**Motor lifetime:** Approx. 10,000 hrs.  
**Heater lifetime:** Approx. 800 hrs.  
**Accessories:** Use of our professional accessories

**Dimensions:** 14.10" x 3.60" x 3.70" (l x w x h)  
**Net Weight:** 1.85 lbs (29.63oz)  
**Single Sell Pack Box :** Dimensions: 17.13" x 4.13 " x 4.13"  
 Weight: 3.26 lbs (52.10 oz)  
**Single Sell Pack Case:** Dimensions: 15.35" x 4.33" x 12.6"  
 Weight: 5.17 lbs (82.65 oz)  
**Country of origin:** Romania  
**Warranty:** One year limited



UPC-Code	Prod. No.	Version
018139376002	110025600	Box
018139376019	110047485	Case



RoHS  
Compliant



double insulated

**ISO**  
9001:  
2015  
14001:  
2015