

TSHL600-27K-12V-R16-KIT  
 TSHL600-30K-12V-R16-KIT  
 TSHL600-52K-12V-R16-KIT

## 4.4W White LED Tape Light Kit, High Output

### SPECIFICATION:

<b>Input Voltage</b>	12 VDC
<b>Wattage</b>	4.4 W/ft
<b>Output</b>	<div style="display: flex; align-items: center;"> <div style="width: 15px; height: 15px; background-color: #FFD700; margin-right: 5px;"></div> 2700K - 320 lm/ft  <div style="width: 15px; height: 15px; background-color: #FFFF00; margin-right: 5px; margin-top: 2px;"></div> 3000K - 329 lm/ft  <div style="width: 15px; height: 15px; background-color: #ADD8E6; margin-right: 5px; margin-top: 2px;"></div> 5200K - 395 lm/ft         </div>
<b>CRI</b>	90+
<b>Dimmable</b>	0-10V, ELV, MLV
<b>Max. Run Length</b>	16 ft
<b>Field Cuttable</b>	2" cut points
<b>Beam Angle</b>	120°
<b>LED Tape Operating Temp.</b>	-13 °F to 140 °F
<b>LED Tape Warranty</b>	5 year limited*
<b>LED Tape Lifetime</b>	50,000 hours
<b>LED Tape Adhesive</b>	3M™ VHB mounting adhesive on back
<b>LED Tape Dimensions</b>	0.39" W x 0.08" H (10mm x 2mm)
<b>IP Rating</b>	IP20 - dry locations onlu
<b>Incl. Power Supply</b>	120VAC to 12VDC, 72W Capacity



HIGH QUALITY LED LIGHTING KITS



### Applications:

- Indoor signage
- Indirect lighting
- Accent lighting
- Undercabinet
- Furniture accents

### INCLUDED IN KIT



**TSHL600-XX-12V-R16  
16FT TAPELIGHT REEL**

1 OF EACH



**P72W12V  
12V POWER SUPPLY**

1 OF EACH



**GRIPPER-TT-SC  
GRIPPER-TW-SC**

2 OF EACH

TSHL600-27K-12V-R16-KIT  
TSHL600-30K-12V-R16-KIT  
TSHL600-52K-12V-R16-KIT

## 4.4W White LED Tape Light Kit, High Output

### WIRING DIAGRAM:

