

### **SOLISTRAND**

TE Internal #: 330367

Splices, Butt Splice, 22 – 16 AWG Wire Size, .3 – 1.42 mm² Wire Size, Serrated, .061 in [1.55 mm] Barrel Inside Diameter, 509 – 3260

CMA Wire Size

View on TE.com >



Terminals & Splices > Splices











Wire Size: .3 – 1.42 mm<sup>2</sup>

Sealable: No

Splice Features: Serrated

Barrel Inside Diameter: 1.55 mm [ .061 in ]

# **Features**

# **Product Type Features**

Splice Accessory Type	Splice
Sealable	No
Splice Type	Butt Splice
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Non-Insulation Support

## **Configuration Features**

Number of Serrations	16
Compatible With Wire & Cable Type	Discrete Wire

# **Body Features**

Splice Features	Serrated	
Contact Features		

Terminal Plating Thickness	2.54 μm[100 μin]
Terminal Plating Material	Tin
Contact Base Material	Copper



Barrel Type	Closed
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
Recovered Inside Diameter	1.55 mm[.061 in]
Outside Diameter	3.58 mm[.141 in]
Wire Size	509 – 3260 CMA
Barrel Inside Diameter	1.55 mm[.061 in]
Terminal Material Thickness	.84 mm[.033 in]
Product Length	14.68 mm[.578 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	170 °C[338 °F]
Operation/Application	
Compatible With Wire Base Material	Copper
Industry Standards	
Government Qualified Splice	No
Packaging Features	
Packaging Quantity	1000
Packaging Method	Loose Piece
Other	
Terminals & Splices Comment	Marking: Commercial 22-16- Military 22-18 in accordance with MIL-T-7928.

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC



Halogen Content Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not applicable for solder process capability

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

# Compatible Parts



SOLISTRAND 10-22 DIE ASSY



TE Part # 58546-1 PC 22-10 SOLISSPICE SPL I SHT




DAHT SOLIS 22-10 ASSY





TE Part # 58545-3 SDE DIE ASSY. 22-10 SOLISTRAND



TE Part # 47812 DIES SOLIS 22-16 DIE SET



MATR SOLISTR 0,3-6,



TE Part # 58545-4 SOLISTRAND 10-22 DIE ASSY.


# **Customers Also Bought**

















### **Documents**

Product Drawings
SPLICE, SOLIS BUTT 22-16

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_330367\_C.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_330367\_C.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_330367\_C.3d\_stp.zip

English

3D PDF

English

**Customer View Model** 

ENG\_CVM\_330367\_D.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_330367\_D.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_330367\_D.2d\_dxf.zip

English

Splices, Butt Splice, 22 – 16 AWG Wire Size, .3 – 1.42 mm² Wire Size, Serrated, .061 in [1.55 mm] Barrel Inside Diameter, 509 – 3260 CMA Wire Size



By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

# Datasheets & Catalog Pages

Datasheet - Ev-Charging Electrical

English

# Agency Approvals

**UL Report** 

English