



- NOTES:**
1. RoHS COMPLIANT
 2. FOR WAVESOLDERING (SOLDER BATH TEMPERATURE 260°C FOR 5 SEC. AND SOLDER PREHEAT 100°C FOR 30 SEC.)
 3. METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
 4. INSULATORS: HIGH TEMPERATURE PLASTIC UL 94 V-0, BLACK
 5. CONTACTS: COPPER ALLOY; PLATING (SEE PART NO.):
 PLEASE ADD A for GOLD FLASH over NICKEL (PREFERRED TYPE)
 PLEASE ADD B for 20µm HARD GOLD over min. 50µm NICKEL
 PLEASE ADD C for 30µm HARD GOLD over min. 50µm NICKEL
 CONTACTS TAILS PRETINNED
 6. THREADED INSERTS: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
 7. COLLARS: COPPER ALLOY; min 200µm TIN over 80µm NICKEL
 8. DIELECTRIC WITHSTANDING VOLTAGE: 300 VDC
 9. CAPACITANCE: 830pF ± 20%
 10. MAXIMUM TORQUE VALUE FOR THREAD: 6 in. LB
 11. CONNECTOR IS PART MARKED: 241□16520X CONEC ABC (see note 5)

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm		scale: 2:1 (5:1)
					material: SEE NOTES
	date	name	title: D-SUB HD FILTER MALE 44pos. SOLDER PIN STRAIGHT with threaded insert		
	drawn 21.06.13 Henenboel	appd. 21.06.13 Fischer			
norm	d-old	dwg no:		DIN-A3	
a Original				sh: 1	
rev.	description			date	name

Directive 2002/95/EC RoHS compliant