# 1744417-9 ACTIVE

### Economy Power 2.5

TE Internal #: 1744417-9

Housing, Receptacle, Wire-to-Board, 9 Position, .098 in [2.5 mm] Centerline, Crimp, 1 Row, Natural, Mating Retention, Wire & Cable,

Economy Power 2.5

View on TE.com >





Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings











Connector Product Type: Housing

Connector & Housing Type: Receptacle

Connector System: Wire-to-Board

Number of Positions: 9

Centerline (Pitch): 2.5 mm [ .098 in ]

### **Features**

### **Product Type Features**

Connector Product Type	Housing
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	9
Number of Rows	1
Electrical Characteristics	
Operating Voltage	250 VAC
Body Features	
Primary Product Color	Natural
Contact Features	



Contact Type  Termination Features  Termination Method to Wire & Cable  Mechanical Attachment  Strain Relief  Panel Mount Feature  Without  PCB Mount Retention  Mating Retention Type  Latch  Mating Retention With  Connector Mounting Type  Housing Features  Housing Fentry Configuration  Housing Material  Centraline (Pitch)  Dimensions  Connector Length	Contact Layout	Inline
Termination Method to Wire & Cable  Mechanical Attachment  Strain Relief Without  Panel Mount Feature Without  PCB Mount Retention Without  Mating Retention Type Latch  Mating Retention Type Cable Mount (Free-Hanging)  Housing Retention  Housing Features  Housing Entry Configuration Both Ends Closed  Housing Material Nylon  Centerline (Pitch) 2.5 mm[.098 in]  Dimensions  Connector Length 24.8 mm[.975 in]  Connector Height 5.7 mm[.224 in]  Usage Conditions  Operating Temperature Range -55 – 105 °C[-67 – 221 °I]  Operation/Application  Circuit Application Power  Industry Standards  Glow Wire Rating Glow Wire  UL Planmrability Rating UL 94V-0  Packaging Peatures  Packaging Quantity 500	Contact Type	Socket
Mechanical Attachment  Strain Relief Without  Panel Mount I eature Without  PCB Mount Retention Without  Mating Retention Type Latch  Mating Retention With  Connector Mounting Type Cable Mount (Free Hanging)  Housing Features  Housing Features  Housing Entry Configuration Both Ends Closed  Housing Material Nylon  Centerline (Pitch) 2.5 mml.098 in]  Dimensions  Connector Length 24.8 mml.975 in]  Connector Height 5.7 mml.224 in]  Usage Conditions  Operating Temperature Range 55 – 105 °Cl. 67 – 221 °F]  Operation/Application Power  Industry Standards  Glow Wire Rating Glow Wire  UL Flammability Rating UL 94V-0  Packaging Features  Packaging Features	Termination Features	
Strain Relief Without Panel Mount Feature Without PCB Mount Retention Without Mating Retention Type Latch Mating Retention With Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Features Housing Entry Configuration Both Ends Closed Housing Material Nylon Centerline (Pitch) 2.5 mm[.098 in]  Dimensions  Connector Length 24.8 mm[.975 in] Connector Height 5.7 mm[.224 in]  Usage Conditions  Operating Temperature Range .55 – 105 °C[.67 – 221 °F]  Operation/Application Circuit Application  Circuit Application Power Industry Standards Glow Wire Rating Glow Wire UL Flammability Rating UL 94V-0  Packaging Quantity 500	Termination Method to Wire & Cable	Crimp
Panel Mount Feature  PCB Mount Retention  Without  Mating Retention Type  Latch  Mating Retention  With  Connector Mounting Type  Cable Mount (Free Hanging)  Housing Features  Housing Features  Housing Entry Configuration  Both Ends Closed  I lousing Material  Nylon  Centerline (Pitch)  2.5 mm[.098 in]  Dimensions  Connector Length  Connector Height  5.7 mm[.274 in]  Usage Conditions  Operating Temperature Range  -55 – 105 °C[-67 – 221 °F]  Coperation/Application  Circuit Application  Power  Industry Standards  Glow Wire  UL Flammability Rating  UL 94V-0  Packaging Features  Packaging Quantity  500	Mechanical Attachment	
PCB Mount Retention Mating Retention Type Latch Mating Retention With Connector Mounting Type Cable Mount (Free-Hanging)  Housing Features  Housing Entry Configuration Both Ends Closed Nylon Centerline (Pitch) 2.5 mm[.098 in]  Dimensions  Connector Length 24.8 mm[.975 in] Connector Height 5.7 mm[.224 in]  Usage Conditions  Operating Temperature Range -55 – 105 °C[ 67 – 221 °F]  Operation/Application Circuit Application Power  Industry Standards Glow Wire UL Flammability Rating UL 94V-0  Packaging Features Packaging Quantity 500	Strain Relief	Without
Mating Retention Type  Mating Retention  With  Connector Mounting Type  Cable Mount (Free-Hanging)  Housing Features  Housing Eatures  Housing Material  Nylon  Centerline (Pitch)  Dimensions  Connector Length  Connector Height  Usage Conditions  Operating Temperature Range  Circuit Application  Circuit Application  Glow Wire Rating  UL Plammability Rating  Packaging Features  Packaging Guantity  Latch  With  With  Cable Mount (Free-Hanging)  Both Ends Closed  Nylon  24.8 mm[.978 in]  24.8 mm[.975 in]  5.7 mm[.224 in]  Power  Fower  Industry Standards  Glow Wire  UL 94V 0  Packaging Features  Packaging Quantity	Panel Mount Feature	Without
Mating Retention With Connector Mounting Type Cable Mount (Free-Hanging)  Housing Features  Housing Entry Configuration Both Ends Closed  Housing Material Nylon Centerline (Pitch) 2.5 mm[.098 in]  Dimensions  Connector Length 24.8 mm[.975 in] Connector Height 5.7 mm[.224 in]  Usage Conditions  Operating Temperature Range -55 - 105 °C[-67 - 221 °F]  Operation/Application  Circuit Application Power  Industry Standards  Glow Wire Rating Glow Wire  UL Flammability Rating UL 94V-0  Packaging Features  Packaging Quantity 500	PCB Mount Retention	Without
Connector Mounting Type  Cable Mount (Free-Hanging)  Housing Features  Housing Entry Configuration  Housing Material  Nylon  Centerline (Pitch)  Dimensions  Connector Length  Connector Height  Usage Conditions  Operating Temperature Range  S5 - 105 °C[ 67 - 221 °F]  Operation/Application  Circuit Application  Power  Industry Standards  Glow Wire Rating  UI. Flammability Rating  Packaging Features  Packaging Quantity  S both Ends Closed  Nylon  24.8 mm[.975 in]  5.7 mm[.224 in]  Val.8 mm[.975 in]  Connector Height  St. Tom[.224 in]  Usage Conditions  Glow Wire  UI. Flammability Rating  UI. 94V-0  Packaging Features  Packaging Quantity	Mating Retention Type	Latch
Housing Features  Housing Entry Configuration  Housing Material  Nylon  Centerline (Pitch)  Dimensions  Connector Length  Connector Height  Usage Conditions  Operating Temperature Range  Operation/Application  Circuit Application  Power  Industry Standards  Glow Wire Rating  UL Flammability Rating  Packaging Quantity  Both Ends Closed  Nylon  Nylon  2.5 mm[.098 in]  24.8 mm[.975 in]  5.7 mm[.224 in]  Usage Conditions  Power  Glow Wire  UL 94V-0  Packaging Features  Packaging Quantity	Mating Retention	With
Housing Entry Configuration Housing Material Nylon  Centerline (Pitch) 2.5 mm[.098 in]  Dimensions  Connector Length Connector Height 5.7 mm[.224 in]  Usage Conditions  Operating Temperature Range -55 – 105 °C[-67 – 221 °F]  Operation/Application  Circuit Application  Power  Industry Standards  Glow Wire Rating UL Flammability Rating UL P4V-0  Packaging Features  Packaging Quantity  500	Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Material Nylon  Centerline (Pitch) 2.5 mm[.098 in]  Dimensions  Connector Length 24.8 mm[.975 in]  Connector Height 5.7 mm[.224 in]  Usage Conditions  Operating Temperature Range -55 – 105 °C[-67 – 221 °F]  Operation/Application  Circuit Application Power  Industry Standards  Glow Wire Rating Glow Wire  UL Flammability Rating UL 94V-0  Packaging Features  Packaging Quantity 500	Housing Features	
Centerline (Pitch)  Dimensions  Connector Length  Connector Height  Connector Height  Usage Conditions  Operating Temperature Range  Operation/Application  Circuit Application  Power  Industry Standards  Glow Wire Rating  UL Flammability Rating  Packaging Features  Packaging Quantity  2.5 mm[.098 in]  24.8 mm[.098 in]  5.7 mm[.224 in]  5.7 mm[.224 in]  For packaging injection  Government of the properties	Housing Entry Configuration	Both Ends Closed
Dimensions  Connector Length 24.8 mm[.975 in] Connector Height 5.7 mm[.224 in]  Usage Conditions  Operating Temperature Range -55 – 105 °C[-67 – 221 °F]  Operation/Application  Circuit Application Power  Industry Standards  Glow Wire Rating Glow Wire  UL Flammability Rating UL 94V-0  Packaging Features  Packaging Quantity 500	Housing Material	Nylon
Connector Length Connector Height 5.7 mm[.224 in]  Usage Conditions  Operating Temperature Range -55 - 105 °C[-67 - 221 °F]  Operation/Application  Circuit Application  Power  Industry Standards  Glow Wire Rating UL Flammability Rating UL 94V-0  Packaging Features  Packaging Quantity  500	Centerline (Pitch)	2.5 mm[.098 in]
Connector Height  Usage Conditions  Operating Temperature Range  -55 - 105 °C[-67 - 221 °F]  Operation/Application  Circuit Application  Power  Industry Standards  Glow Wire Rating  UL Flammability Rating  UL 94V-0  Packaging Features  Packaging Quantity  500	Dimensions	
Usage Conditions  Operating Temperature Range -55 – 105 °C[-67 – 221 °F]  Operation/Application  Circuit Application Power  Industry Standards  Glow Wire Rating Glow Wire  UL Flammability Rating UL 94V-0  Packaging Features  Packaging Quantity 500	Connector Length	24.8 mm[.975 in]
Operating Temperature Range -55 – 105 °C[-67 – 221 °F]  Operation/Application  Circuit Application Power  Industry Standards  Glow Wire Rating Glow Wire  UL Flammability Rating UL 94V-0  Packaging Features  Packaging Quantity 500	Connector Height	5.7 mm[.224 in]
Operation/Application  Circuit Application  Power  Industry Standards  Glow Wire Rating  UL Flammability Rating  UL 94V-0  Packaging Features  Packaging Quantity  500	Usage Conditions	
Circuit Application Power  Industry Standards  Glow Wire Rating Glow Wire  UL Flammability Rating UL 94V-0  Packaging Features  Packaging Quantity 500	Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Industry Standards  Glow Wire Rating  UL Flammability Rating  UL 94V-0  Packaging Features  Packaging Quantity  500	Operation/Application	
Glow Wire Rating  UL Flammability Rating  Packaging Features  Packaging Quantity  Glow Wire  UL 94V-0  500	Circuit Application	Power
UL Flammability Rating  Packaging Features  Packaging Quantity  500	Industry Standards	
Packaging Features  Packaging Quantity  500	Glow Wire Rating	Glow Wire
Packaging Quantity 500	UL Flammability Rating	UL 94V-0
	Packaging Features	
Packaging Method Bag	Packaging Quantity	500
	Packaging Method	Bag

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant	
LO ROLIS DITECTIVE ZOTI/03/LO	Compilant	



EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

### **Compatible Parts**






















TE Part # 1744446-9 Hdr Assy, EP 2.5 RA, 9 Pos., GW



TE Part # 2-2365497-9 EP2.5 single row SMT header,9P,red



TE Part # 2365497-9 EP2.5 single row SMT header, GWT, 9P



TE Part # 2404280-9 EP 2.5 HDR, GLOW WIRE, 9P



TE Part # 3-2365497-9 EP2.5 single row SMT header,9P,green



TE Part # 4-2365497-9 EP2.5 single row SMT header,9P,blue



TE Part # 6-2365497-9 EP2.5 single row SMT header,9P,black



TE Part # 8-2365497-9 EP2.5 single row SMT header,9P,yellow

# Also in the Series | Economy Power 2.5









& Housings(311)



Wire-to-Board Connector Contacts(6)

## Customers Also Bought



TE Part #1565084-1 GRACE INERTIA CONNECTOR 3.5 6P



TE Part #1565086-1 GRACE INERTIA CONNECTOR 3.5 3P




TE Part #1744416-7 7 POS EP II HSG, GLOW WIRE



TE Part #176498-1 POSITIVE LOCK 187 (4.8 MM) HOUSING





TE Part #1903392-1 GIC 2.5 W CAP HSG 3P NATURAL



TE Part #1744417-7 7 POS EP 2.5 HSG, GLOW WIRE









#### **Documents**

### **Product Drawings**

9 POS EP 2.5 HSG, GLOW WIRE

English

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1744417-9\_D.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1744417-9\_D.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1744417-9\_D.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

### Datasheets & Catalog Pages

7-1773461-6\_EP2.5\_Connector\_Series

English

### **Product Specifications**

**Application Specification** 

English

### **Product Environmental Compliance**

**TE Material Declaration** 

Housing, Receptacle, Wire-to-Board, 9 Position, .098 in [2.5 mm] Centerline, Crimp, 1 Row, Natural, Mating Retention, Wire & Cable, Economy Power 2.5



English

Agency Approvals

**UL Report** 

English