



Components:

- A. 0.080" thick, 1.50" wide, dual layer rubber, black conductive exterior with a non-marring interior. Tear resistant nylon reinforced 4.3 oz. inner scrim layer prevents the rubber from tearing.
- B. 3/8" wide, 30" long blue polyester tab contains electrically conductive carbon suffused fibers.
- C. 3/4" wide blue elastic material stretches for comfort.
- D. Adjustable snap-loc fastening system.
- E. A 1/4 watt, 2 megohm resistor.
- F. Stretch elastic back.

listed and date coded.

Electrical Properties

Property	Test Method	Value
Flooring contact surface (sole) to body contacting surface (tab) resistance.	ANSI/ESD STM97.1, ESD SP9.2, ESD TR53	< 1 x 10 ⁹ ohms

Item	17239	17240	17241	17242	17243
Size	XSmall	Small	Medium	Large	XLarge
Shoe Size Women	5 - 7	6 - 8	7 - 9	8 - 11	11+
Shoe Size Men	N/A	6 - 9	8 - 11	10 - 13	12+

Recommended sizing. Request samples [HERE](#).

RoHS 2, REACH, and Conflict Minerals Statement
 None of the RoHS 2 restricted materials, or REACH substances of very high concern as of 2015/06/15, or Conflict Minerals are intentionally added in manufacturing this product. Ref: European Union Directive 2011/65/EU and Regulation (EC) No. 1907/2006/CE. See Desco Limited Warranty at [Desco.com](#).

For additional information on the use and maintenance of foot grounders please ask for Technical Bulletin [TB-2020](#).



Made in the United States of America

Specifications and procedures subject to change without notice.

SOLE GROUNDERS WITH SNAP-LOC

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710
 WEB SITE: [Desco.com](#) PHONE (909) 627-8178 FAX (909) 627-7449
 DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407
 PHONE (781) 821-8370 FAX (781) 575-0172

DRAWING NUMBER
17239

DATE:
January 2016

