

6 5 4 3 2 1

APPROVED: _____
DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	2/22/21	

RECOMMENDED PCB LAYOUT

SPECIFICATIONS:

Material:
Insulator: PA, rated UL 94V-0
Insulator color: Green
Pin Header: Copper Alloy, Tin plated

Electrical:
Voltage rating: 600 V
Current rating: 51 A
Dielectric withstanding voltage: 2,200 V for 1 minute

Mechanical:
Wire range: 18~4AWG
Wire strip length: 17-18mm
Temperature Rating:
Operating temperature: -40°C to +105°C
Environmental:
Lead free, RoHS compliant.

Positions: 02 thru 18
A= .591 [15.00] x No. of Space + .449 [11.40]
B= .591 [15.00] x No. of Space

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED INCHES HOLES .X ± .10 Ø.X ± .10 .XX ± .020 Ø.XX ± .015 .XXX ± .015 Ø.XXX ± .010		ADAM TECH 909 Rahway Avenue, Union, NJ 07083 Phone: 908-687-5000 Fax: 908-687-5710	
APPROVALS DRAWN LH 2/22/21 CHECKED NL 2/22/21 APPROVED		DATE DATE DATE	
TITLE .591[15.00] PITCH SPRING CLAMP TERMINAL BLOCKS, RIGHT ANGLE		SIZE X	PART NO. EB171A-XX-K
REF: S00067C		SCALE: NTS	SHEET 1 OF 1

6 5 4 3 2 1