18 INCHES LENGTH



Connector A 132176 SMA Jack Straight Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-316DB Continuity/Hi-Pot Connector B 122358-10 TNC Jack Straight Bulkhead - Rear Mount Brass Nickel IP67 + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

| | Connector A | | | Cable | | | Connector B | | |
|---|---|---|--|---|--|--|---|--|--|
| | Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: | 132176 SMA BHD JK RG316 DB 500 SMA Jack Straight Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Gold None Beryllium Copper Gold 12.4 GHz SMA Jack Straight BHD | | Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length: | RG-316DS RG-316DB - ST 0.102 ST Double Braid 0.102 50 Ohm None Continuity Hi-Pot 18 Inches | Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking: | 122358-10 TNC BHD JK RG31 TNC Jack Straight Crimp Standard 50 Ohm Bulkhead - Rear Mo Brass Nickel IP67 Phosphor Bronze Gold 11 GHz TNC Jack Straight E 0° | unt | |
| Amphenol CUSTOM CABLE CONTROLLED DOCUMENT DO NOT CORV CUSTOM CABLE | | | THIS DRAWING MAY CONTAIN PROPRIETARY INFORMATION / FOR ANY PURPOSE DETRIMEN INC. IT MAY NOT BE REPRODU- IN ANY FORM WITHOUT THE W CUSTOM CABLE INC. ACCEPTA ESTABLISHES AND AGREEMEN | AND MUST NOT BE USED ITAL TO CUSTOM CABLE JCED OR TRANSCRIBED WRITTEN CONSENT OF ANCE OF THIS DRAWING Part No: | | Г-JK G316D 18I | | UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES | |



RoHS 2015/863 Compliance Statement

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/2/2023

Part Number: Q-2X04H000R018I

Manufacturer: Amphenol Custom Cable

Description: SMA-ST-JK/TNC-ST-JK G316D 18I

This information is valid as of the date indicated for the item (part number) listed.

Director of Quality Assurance

Janice Frank