


FAKRA Generation 1 – Code L for RG-174/RG-316/TGC-1.5DS/(TGC/CFD200 cables)



Product description

Taoglas is a leading provider of advanced technology for a smarter world. Our solutions include advanced components and technologies and help OEMs, enterprises, and communities to resolve the complexities of bringing digital transformation solutions to market quickly and cost effectively. Focused on best-in-class, high-performance antenna and RF design with advanced positioning, imaging, audio and artificial intelligence technologies, Taoglas understands the importance of high-performance connections.

Taoglas GEN.1 FAKRA connectors utilize a metal SMB connector embedded within a plastic enclosure that is colour coded and keyed for ease of identification and assembly. They have been designed with a swivel style housing for ease of installation. They are designed for high-volume production, automated harness assembly and provide superior performance. They are manufactured with the highest precision and are thoroughly tested to meet USCAR-2 and USCAR-17 standards. All Taoglas connectors are RoHS & REACH compliant.

The Carmine Red Code L connector is typically used Auxiliary connections (often cellular MIMO 2) and is available in both Jack and Plug and for multiple cable diameters.

Features

- Optimized for automated manufacturing
- Full Series of colours available
- RF performance up to 6GHz
- Primary and Secondary Locks
- Tulip contact/ anti-stubbing
- Housing inner ring/ anti-scooping
- Fully compliant to USCAR requirements

Specifications


| Electrical | |
|---|--|
| Impedance | 50Ω Nominal |
| Frequency Range | DC - 6000MHz |
| VSWR (Return Loss) | 0 ~ 3000MHz < 1.3 3000 ~ 6000MHz < 1.5 |
| D.W.V | 800 VRMS, Min |
| Insulation Resistance | ≥100MΩ |
| Mechanical | |
| Durability | 25 Cycles Min |
| Insertion Force | ≤25N |
| Withdraw Force | ≥2N |
| Locking Device Strength | ≥80N |
| Outer Contact Retention Force in Housing | ≥100N |
| Suitable Cables | TGC-1.5DS, RG-174, RG-316, TGC/CFD200 |
| Storage and Operational Temperature Range | -40°C - 105°C |



FAKRA Code L - Carmine Red

Mechanical Drawings

FK1FLDK - Code L Female Jack for RG-174/RG-316/TGC-1.5DS



FK0MLDK - Code L Male Plug for RG-174/RG-316/TGC-1.5DS

FK1FLG - Code L Female Jack for TGC/CFD200

FK0MLG - Code L Male Plug for TGC/CFD200