


Wire Range	Insulation Diameter	Reel Q'ty
AWG #22~#28	1.50 MAX. (.059)	10,000 PCS.


Ordering Code

$\frac{CI31}{①}$
 $\frac{T02}{②}$
 $\frac{*}{③}$
 $\frac{*}{④}$
 $\frac{E}{⑤}$
 $\frac{0}{⑥}$

- ① Series No.
- ② Type: T02 = AWG #22 ~ #28
- ③ Plating: 1 = 1.52 μ m(60 μ) Min. Tin over 0.38 μ m(15 μ) Nickel
 A = Selective Gold Flash Plated over 1.27 μ m(50 μ) Nickel
 B = Selective 0.38 μ m(15 μ) gold plated over 1.27 μ m(50 μ) Nickel
- ④ Material: B = Brass
 P = Phosphor Bronze
- ⑤ Plating method: E = Pre-tinned
- ⑥ Option: 0 = Standard




SEC: A-A



SEC: B-B

RoHS Compliant

SYMBOL	NAME	DATE	REVISIONS	APPROVED BY:	DATE	UNIT: mm / inch	TITLE: 2.54MM(.100") CRIMP TERMINAL	 瀚荃股份有限公司 CviLux Corporation
⑤	Karen	4/07-20	ECNT120089/ECRB120007					
④	Erin	5/7-12	ECR12021-0/ECN12074-0	DRAWN BY: Karen	4/13-20	TOLERANCE UNLESS OTHERWISE SPECIFIED		
③	Una	04/20-11	ECN11074	ENGINEER: Sun	4/13-20	.X ± 0.20/.008 X' ± 1"	MATERIAL:	
②	EDDY	10/23/03	ECN03367, ECR03013-1	CHECKED BY: Eisley	4/13-20	.XX ± 0.10/.004 .X' ±	FINISH:	
				APPROVED BY: Eisley	4/13-20	.XXX ± 0.05/.002 .XX' ±		

CIVIL UX
 2020.04.16
 ISSUED

DRAWING NO.	CI3105SK	PART NO.	CI31T02**E0
SCALE	5 / 1	SHEET	1 OF 1