
STATSHIELD® 81705 SERIES





Specifications:

Standard Document MIL-PRF-81705E

Electrical Properties

MIL-DTL-117H

Static Decay

Meets Requirements of:

Type III, Class 2

Type II, Class H, Style 2

Test Procedures/Method

Surface Resistance: $< 1 \times 10^{12} \text{ ohms/sa}$ Outer Surface $\geq 1 \times 10^5 \text{ to } < 1 \times 10^{12} \text{ ohms/sq}$ Inner Surface Discharge Shielding ≤ 10 nJ **EMI** Attenuation

≥ 10 db

≤ 2 seconds

2.8 mils, 0.071 mm ± 10%

Typical Values

MIL-PRF-81705E, 4.6.8 MIL-PRF-81705E, 4.6.8 MIL-PRF-81705E, 4.6.9 MIL-PRF-81705E, 4.6.7 MIL-STD-3010, 4046

Physical Properties

Film Thickness **Tensile Strenath** Puncture Resistance Non-corrosive Marking Abrasion Resistance Transparency

4600 PSI, 32 MPa 12 lbs, 53 N Pass Pass 40%


MIL-STD-3010, 1003

ASTM D882

MIL-STD-3010, 2065 MIL-STD-3010. M3005* MIL-PRF-81705E. 4.6.6 MIL-STD-3010, 4034

Heat Sealing Conditions

Temperature 360°F, 182°C 2 seconds Time 60 PSI, 414 KPa Pressure



Markings: Group A

Material identification printed between polyester and aluminum shielding layer. Specification number, type, class, manufacturer's name, manufacturer's designation, month and year of manufacture, lot number and heat sealing conditions (temperature, pressure and dwell time). Not shown to scale. Color: black. Appears every 6 inches along length of the material. Meets marking requirements of MIL-PRF-81705E: 3.6

Group B

Identification hot stamped or thermally printed on surface layer. Specification number, revision letter. type, class, manufacturer's name, manufacturer's designation, and lot number. Not shown to scale. Color: yellow. Meets marking requirements of MIL-DTL-117H: 3.5 for converted bags.

This product is on the Qualified Product Listing under the Defense Standardization Program. Check our listing here.

*Passes on all surfaces noted in MIL-PRF-81705E Special Requirement 6/ Bag is free of silicones and heavy metals. Specifications and procedures subject to change without notice.

Note: Default hot stamp color is vellow. Artwork not to scale.

RoHS, REACH, and Conflict Minerals Statement See the Desco Industries RoHS. REACH, and Conflict Minerals Statement:

https://desco.descoindustries.com/pdf/Regulatory Statements Desco Statshield Bags.pdf

See the Desco Limited Warranty:

http://desco.descoindustries.com/Limited-Warranty.aspx



DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com PHONE (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370

DRAWING NUMBER 12910

DATE September 2021

Made in the

United States of America

