

Multi-range Timer S1DXM-A / S1DXM-M



S1DXM-A/M Multi-range Timer



Features

- Multiple functions built in
- Model No. consolidation (The lineup consists of 64 easy-to choose models)
- Cadmium-free contacts used
- Operation mode and time range switches are on front panel (Operation mode switch on S1DXM-M series only)
- Reasonable price

Compact analog timers featuring multi-functions

S1DXM-A multi-range timer (Power ON-delay type),
S1DXM-M multi-range timer (4 operation mode type)

Time selectable Mode selectable IP40

PRODUCT TYPES

S1DXM-A multi-range timer without MODE switch

Operation mode (fixed): Power ON-delay

Operating voltage	Time range	Timed-out 2 Form C		Timed-out 4 Form C	
		Model No.		Model No.	
12 V DC	0.05 s to 10 min	S1DXM-A2C10M-DC12V		S1DXM-A4C10M-DC12V	
	0.2 s to 30 min	S1DXM-A2C30M-DC12V		S1DXM-A4C30M-DC12V	
	0.5 s to 60 min	S1DXM-A2C60M-DC12V		S1DXM-A4C60M-DC12V	
	0.05 min to 10 hr	S1DXM-A2C10H-DC12V		S1DXM-A4C10H-DC12V	
24 V DC	0.05 s to 10 min	S1DXM-A2C10M-DC24V		S1DXM-A4C10M-DC24V	
	0.2 s to 30 min	S1DXM-A2C30M-DC24V		S1DXM-A4C30M-DC24V	
	0.5 s to 60 min	S1DXM-A2C60M-DC24V		S1DXM-A4C60M-DC24V	
	0.05 min to 10 hr	S1DXM-A2C10H-DC24V		S1DXM-A4C10H-DC24V	
100 to 120 V AC	0.05 s to 10 min	S1DXM-A2C10M-AC120V		S1DXM-A4C10M-AC120V	
	0.2 s to 30 min	S1DXM-A2C30M-AC120V		S1DXM-A4C30M-AC120V	
	0.5 s to 60 min	S1DXM-A2C60M-AC120V		S1DXM-A4C60M-AC120V	
	0.05 min to 10 hr	S1DXM-A2C10H-AC120V		S1DXM-A4C10H-AC120V	
200 to 220 V AC	0.05 s to 10 min	S1DXM-A2C10M-AC220V		S1DXM-A4C10M-AC220V	
	0.2 s to 30 min	S1DXM-A2C30M-AC220V		S1DXM-A4C30M-AC220V	
	0.5 s to 60 min	S1DXM-A2C60M-AC220V		S1DXM-A4C60M-AC220V	
	0.05 min to 10 hr	S1DXM-A2C10H-AC220V		S1DXM-A4C10H-AC220V	

Note: 48 V DC, 100 to 110 V DC, 24 V AC and 220 to 240 V AC types are made to order. Please inquire for details.
A socket line holding clip (ADX28005) is not included with the product. Please purchase separately.

S1DXM-M multi-range timer with MODE switch

Operation mode (switchable): Power ON-delay, Power Flicker OFF start, Power Flicker ON start, Power One-shot

Operating voltage	Time range	Timed-out 2 Form C		Timed-out 4 Form C	
		Model No.		Model No.	
12 V DC	0.05 s to 10 min	S1DXM-M2C10M-DC12V		S1DXM-M4C10M-DC12V	
	0.2 s to 30 min	S1DXM-M2C30M-DC12V		S1DXM-M4C30M-DC12V	
	0.5 s to 60 min	S1DXM-M2C60M-DC12V		S1DXM-M4C60M-DC12V	
	0.05 min to 10 hr	S1DXM-M2C10H-DC12V		S1DXM-M4C10H-DC12V	
24 V DC	0.05 s to 10 min	S1DXM-M2C10M-DC24V		S1DXM-M4C10M-DC24V	
	0.2 s to 30 min	S1DXM-M2C30M-DC24V		S1DXM-M4C30M-DC24V	
	0.5 s to 60 min	S1DXM-M2C60M-DC24V		S1DXM-M4C60M-DC24V	
	0.05 min to 10 hr	S1DXM-M2C10H-DC24V		S1DXM-M4C10H-DC24V	
100 to 120 V AC	0.05 s to 10 min	S1DXM-M2C10M-AC120V		S1DXM-M4C10M-AC120V	
	0.2 s to 30 min	S1DXM-M2C30M-AC120V		S1DXM-M4C30M-AC120V	
	0.5 s to 60 min	S1DXM-M2C60M-AC120V		S1DXM-M4C60M-AC120V	
	0.05 min to 10 hr	S1DXM-M2C10H-AC120V		S1DXM-M4C10H-AC120V	
200 to 220 V AC	0.05 s to 10 min	S1DXM-M2C10M-AC220V		S1DXM-M4C10M-AC220V	
	0.2 s to 30 min	S1DXM-M2C30M-AC220V		S1DXM-M4C30M-AC220V	
	0.5 s to 60 min	S1DXM-M2C60M-AC220V		S1DXM-M4C60M-AC220V	
	0.05 min to 10 hr	S1DXM-M2C10H-AC220V		S1DXM-M4C10H-AC220V	

Note: 48 V DC, 100 to 110 V DC, 24 V AC and 220 to 240 V AC types are made to order. Please inquire for details.
A socket line holding clip (ADX28005) is not included with the product. Please purchase separately.

TIME RANGE SETTING

Type	Time scale	Time unit	Min. scale	Max. scale	Setting range					
					0.05 to 1 s	0.5 to 10 s	0.05 to 1 m	0.5 to 10 m		
S1DXM-A (ADX21 series)	×1	×10	s	m	0.05	1	0.05 to 1 s	0.5 to 10 s	0.05 to 1 m	0.5 to 10 m
			s	m	0.2	3	0.2 to 3 s	2 to 30 s	0.2 to 3 m	2 to 30 m
			s	m	0.5	6	0.5 to 6 s	5 to 60 s	0.5 to 6 m	5 to 60 m
			m	h	0.05	1	0.05 to 1 m	0.5 to 10 m	0.05 to 1 h	0.5 to 10 h
S1DXM-M (ADX27 series)	×1	×10	s	m	0.05	1	0.05 to 1 s	0.5 to 10 s	0.05 to 1 m	0.5 to 10 m
			s	m	0.2	3	0.2 to 3 s	2 to 30 s	0.2 to 3 m	2 to 30 m
			s	m	0.5	6	0.5 to 6 s	5 to 60 s	0.5 to 6 m	5 to 60 m
			m	h	0.05	1	0.05 to 1 m	0.5 to 10 m	0.05 to 1 h	0.5 to 10 h

Note: The time setting range is the combination of the time scale (×1 or ×10) on the dial and the time unit (s, m, or h).
Example: When dial reads 1, time scale is "×1" and time unit is "s", then it is 1 s.

Disclaimer

The applications described in the catalog are all intended for examples only. The purchase of our products described in the catalog shall not be regarded as granting of a license to use our products in the described applications. We do NOT warrant that we have obtained some intellectual properties, such as patent rights, with respect to such applications, or that the described applications may not infringe any intellectual property rights, such as patent rights, of a third party.

Panasonic
INDUSTRY

Panasonic Industry Co., Ltd.

Industrial Device Business Division

7-1-1, Morofuku, Daito-shi, Osaka 574-0044, Japan

industrial.panasonic.com/ac/e/