



* COMPLETELY TIGHTENED

- NOTES:**
- MATERIALS:
 HOOD: PBT GF UL94 V-0 BLACK
 FRONTSEALING: SILICONE VMQ BLUE
 SCREW: STAINLESS STEEL
 O-RING: NBR BLACK
 - TEMPERATURE RANGE: -30°C TO +90°C
 - RECOMMENDED TORQUE FOR SCREW:
 35Ncm (3.1 in.LB)
 MAX. TORQUE: 68Ncm (6 in.LB)
 - SINGLE PACKED

Directive 2002/95/EC RoHS compliant

| | | | | | | | | |
|---|-------------|------------|-------------------------------|--|----------------------------|-------------------------------------|-------------|--|
| THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND | tolerance | | ±0,3 unless otherw. specified | | dim. in mm | scale: | 1,5:1 (1:1) | |
| | | | | | | material: | SEE NOTES | |
| | drawn | 07.02.2014 | Heinrich | | title: | | | |
| | appd. | 07.02.2014 | Huether | | WATER RESISTANT D-SUB HOOD | | | |
| | | | | | | 25 POS. | | |
| | | | | | | SHORT SCREW 4-40UNC STAINLESS STEEL | | |
| | | | | | | dwg no: | | |
| | | | | | | 15K1A1437 | | |
| | | | | | | DIN-A3 | | |
| | | | | | | sh: 1 | | |
| rev. | description | date | name | | | part no: | | |
| | | | | | | 15-004730 | | |