



General ordering data

Order No.	7902100000
Part designation	SAI-ASI-S H 4E/4A
Version	Sensor-actuator active distributor, AS interface, Complete module
EAN	4032248228980
Qty.	1 pc(s).

Technical data of bus system

Bus user	Slave
Diagnosis indication	red
Station addresses	Infrared
Transmission rate	167 kbits

Dimensions

Width	60 mm
-------	-------

Technical data

Behaviour in fire	V-0
Bus system	AS interface
Digital inputs	4
Digital outputs	4
Housing material	Pocan
LED colour for indicating operation	green
Operating temperature, max.	70 °C
Operating temperature, min.	-20 °C
Ordering data, title	SAI-ASI Modular
Pollution severity	3
Protection class	IP 68
Rated voltage	26.5 ...31.6 V
Storage temperature, max.	85 °C
Storage temperature, min.	-40 °C
Total current	2 A
Transmission rate	167 kbits
Version	Mounting hood

Technical data

Technical data, snap-on modules

Digital input type	TYPE 1 to EN 61131-2
E/A function indicator	LED yellow
Insulation material of housing	PBT
Output level	Short-circuit-protected
Sensor voltage indicator	LED green
max. current-carrying capacity per output signal	2 A

Approvals

Approvals institutes



Classifications

ETIM 2.0	EC001430
ETIM 3.0	EC001599
eClass 4.1	27-27-90-12
eClass 5.0	27-27-92-12
eClass 5.1	27-27-92-12

Similar products

Order No.	Part designation	Version
1799280000	SAI-ASI-S H 2E/2A	Sensor-actuator active distributor, AS interface, Complete module
1799270000	SAI-ASI-S H 4A	Sensor-actuator active distributor, AS interface, Complete module
7902090000	SAI-ASI-S H 4E	Sensor-actuator active distributor, AS interface, Complete module