## ATGBICS 3FE53441AC Nokia Compatible Transceiver SFP 2.4Gbs/1.2Gbs-B+ (Tx1490nm/RX1310nm, 20km, SMF, Ind Temp)

Brand: ATGBICS Product code: 3FE53441AC-C

Product name: 3FE53441AC Nokia Compatible Transceiver SFP 2.4Gbs/1.2Gbs-B+ (Tx1490nm/RX1310nm, 20km, SMF, Ind Town)

Ind Temp)

ATCHICS FR CE PER PRINCEPHINI

3FE53441AC Nokia Compatible Transceiver SFP 2.4Gbs/1.2Gbs-B+ (Tx1490nm/RX1310nm, 20km, SMF, Ind Temp)

ATGBICS 3FE53441AC Nokia Compatible Transceiver SFP 2.4Gbs/1.2Gbs-B+ (Tx1490nm/RX1310nm, 20km, SMF, Ind Temp):

ATGBICS 3FE53441AC 2.4/1.2Gbs B+ SFP supports a distance of up to 20km over single mode fibre (SMF) using a wavelength of Tx1590nm/Rx1310nm via an SC connector. This bidirectional unit must be used with another transceiver or network appliance of complimenting wavelengths. This product is suitable for rugged environments and can operate at temperatures between -40C to +85C. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of Nokia3FE53441AC= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Features	
Maximum data transfer rate * 24000 Interface type * SFP+ Single-mode fiber (SMF) supported  Multi-mode fiber (MMF) supported  Fiber optic connector SC SFP transceiver standard BX Maximum transfer distance 20000 Tx wavelength (max) 14900 Rx wavelength (max) 13100 Ethernet LAN Ethernet interface type 25 G	SC BX 20000 m 1490 nm 1310 nm	Brand compatibility Certification	Nokia CE, FCC, RoHS
		Power	
		Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
		Operational conditions	
		Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-40 - 85 °C 0 - 95% 0 - 95%
		Weight & dimensions	
Digital Diagnostics Monitoring (DDM)	×	Width	13.4 mm
<b>Features</b> Product colour	Silver	Depth Height Weight	56.5 mm 8.5 mm 15 g
Housing material Plug and Play Hot-swap Easy to install Country of origin	Metal	Packaging data	
		Number of products included Package type	1 pc(s) Box
		Technical details	
		Sustainability compliance Sustainability certificates Doesn't contain	✓ RoHS Lead



5056468746412

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.