

Termination Insensitive Mixer

Rev. V5

Features

- LO 1 to 3400 MHz
- RF 1 to 3400 MHz
- IF 1 to 2000 MHz
- LO Drive +17 dBm (nominal)
- High Intercept +25 dBm (typ)
- +260° Reflow Compatible

Description

The CSM4T17 is a termination insensitive mixer, designed for use in military, wireless, and test equipment applications. The design utilizes Schottky bridge quad diodes, broadband ferrite baluns and internal loads to provide excellent performance without degradation due to external VSWR mismatches.

Product Image



Ordering Information

| Part Number | Package |
|-------------|---------------|
| CSM4T17 | Surface Mount |







Electrical Specifications: $Z_0 = 50\Omega$ $Lo = +17$ dBm (Downconverter application only)

| Parameter | Test Conditions | Units | Typical | Guaranteed | |
|--------------------------|--|-------|--------------------------------|-------------|---------------|
| | | | | +25°C | -40° to +85°C |
| SSB Conversion Loss(max) | fR = 1 to 2400 MHz, fL = 1 to 2400 MHz, fl = 1 to 2000 MHz fR = 1 to 3400 MHz, fL = 1 to 3400 MHz, fl = 1 to 2000 MHz | dB | 8.0 dB 9.0 dB | 9.0 10.0 | 10.5 11.5 |
| SSB Noise Figure | | dB | Within 1 dB of conversion loss | | |
| L - R Isolation (min) | fL = 1 to 2400 MHz fL = 2400 to 3400 MHz | dB | 35 25 | 25 20 | 23 18 |
| L - I Isolation (min) | fL = 1 to 2400 MHz fL = 2400 to 3400 MHz | dB | 35 25 | 25 20 | 23 18 |
| R - I Isolation (min) | fR = 1 to 3400 MHz | dB | 30 | | |
| 1 dB Conversion Comp. | fL = +17 dBm | dBm | +14 | | |
| Input IP3 | fR1 = 100 to 3400 MHz, fR2 = 100 to 3400 MHz, fL = 50 to 2000 MHz | dBm | +25 | | |
| R-Port VSWR | fR = 1 to 3400 MHz | | 2.0:1 | | |
| L-Port VSWR | fL = 1 to 3400 MHz | | 2.0:1 | | |
| I-Port VSWR | fl = 1 to 2000 MHz | | 2.0:1 | | |


Termination Insensitive Mixer

Rev. V5

Typical Performance Curves



Outline Drawing: Surface Mount *



* Dimensions are inches (millimeters) ± 0.015 (0.38) unless otherwise specified.

Absolute Maximum Ratings

| Parameter | Absolute Maximum |
|-----------------------|--|
| Operating Temperature | -40°C to +85°C |
| Storage Temperature | -65°C to +100°C |
| Peak Input Power | +20 dBm max @ +25°C +17 dBm max @ +85°C |
| Peak Input Current | 50 mA DC |

M/A-COM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with M/A-COM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.