



NOTE
FACE VIEW
ON CONNECTOR

SPECIFICATION
MATERIALS:
 HOUSING: PBT
 INSERT: PBT
 COUPLING: BRASS-NICKEL PLATED
 O-RING: VITON
ELECTRICAL:
 VOLTAGE: 10-30VDC
 CURRENT RATING: 4A PER PORT, 12 AMPS MAX.
 PROTECTION CLASS: IP67
 OPERATING TEMPERATURE: -25°C to +90°C

NOTES:
 FIXING HOLES TO SUIT M4 SCREWS

MATERIAL NUMBER	OLD PART NUMBER
1201140085	BTX803PC

DESCRIPTION EC NO: WEU2010-0450 DRWN: REISSNER 2010/03/22 CHKD: FP APPR: NSTAUDIG 2010/03/23	QUALITY SYMBOLS ▽ = 0 ∇ = 0	GENERAL TOLERANCES (UNLESS SPECIFIED) <table border="1"> <thead> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> </thead> <tbody> <tr> <td>4 PLACES</td> <td>±---</td> <td>±---</td> </tr> <tr> <td>3 PLACES</td> <td>±---</td> <td>±---</td> </tr> <tr> <td>2 PLACES</td> <td>±---</td> <td>±---</td> </tr> <tr> <td>1 PLACE</td> <td>±0.3</td> <td>±---</td> </tr> <tr> <td colspan="3">ANGULAR ± --- °</td> </tr> </tbody> </table>		mm	INCH	4 PLACES	±---	±---	3 PLACES	±---	±---	2 PLACES	±---	±---	1 PLACE	±0.3	±---	ANGULAR ± --- °			DIMENSION STYLE MM ONLY	SCALE 1:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
		mm	INCH																					
	4 PLACES	±---	±---																					
	3 PLACES	±---	±---																					
2 PLACES	±---	±---																						
1 PLACE	±0.3	±---																						
ANGULAR ± --- °																								
DRAWN BY REISSNER	DATE 2010/03/22	MICRO-CHANGE MPIS 8 PORT TOP MOUNT 19POLE M23 MALE CONNECT.																						
CHECKED BY NS	DATE 2010/03/22																							
APPROVED BY NSTAUDIG	DATE 2010/03/23	MOLEX INCORPORATED																						
MATERIAL NO.	DOCUMENT NO. SD-120114-087					SHEET NO. 1 OF 1																		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																					