

9001K53J35LGFG

Harmony 9001K, illuminated selector switch head, metal, long handle, green, 30mm, 3 positions, spring return both sides to center, LED green, 24-28V



Main

| | |
|---------------------------|--------------------------------------|
| Range of Product | Harmony 9001K |
| Product or Component Type | Head for illuminated selector switch |
| Device short name | 9001K |
| Type of operator | To centre spring return |
| Operator profile | Green long handle |

Complementary

| | |
|-------------------------------|------------------------|
| Bezel material | Metal |
| Mounting diameter | 1.18 in (30 mm) |
| Net Weight | 0.54 lb(US) (0.245 kg) |
| Shape of signaling unit head | Octagonal |
| Operator position information | 3 positions |
| Contacts type and composition | Without contact block |
| Mechanical durability | 500000 cycles |
| Light block supply | Direct |
| Light source | LED |
| Bulb base | BA 9s |
| Light block colour | Green |
| [Us] rated supply voltage | 24 V AC/DC |
| Product compatibility | 9001KA1 side 1 or 2 |
| Device presentation | Basic element |

Environment

| | |
|---------------------------------------|--|
| Protective treatment | TC |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C) |
| Electrical shock protection class | Class II IEC 61140 |
| IP degree of protection | IP66 IEC 60529 |
| NEMA degree of protection | NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3R NEMA 4 |
| Standards | JIS C 4520 EN/IEC 60947-5-4 JIS C 852 EN/IEC 60947-5-1 UL 508 CSA C22.2 No 14 EN/IEC 60947-1 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|------------------------|-------------------------------|
| Product Certifications | UL 508 NEMA |
| Vibration resistance | 7 gn 2...500 Hz)IEC 60068-2-6 |
| Shock resistance | 50 gn IEC 60068-2-27 |

Ordering and shipping details

| | |
|-----------------------|-----------------------------|
| Category | 21426-9001 K (NOT KA,KM,KX) |
| Discount Schedule | CS1 |
| GTIN | 3389118042889 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 8.80 oz (249.476 g) |
| Returnability | No |
| Country of origin | MX |

Packing Units

| | |
|------------------------|--------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 1.80 in (4.572 cm) |
| Package 1 width | 2.10 in (5.334 cm) |
| Package 1 Length | 3.60 in (9.144 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|