



NEMA 5-15R
MOLDED CONNECTOR
COLOR: BLACK

CORD STRAIN RELIEF

LENGTH "L"

#12-3 SJTW
300V CORD
COLOR: YELLOW

TECHNICAL:
LISTED: cULus
RATED SUPPLY VOLTAGE: 120 VAC
RATED CURRENT: UP TO 15 AMPS OR CABLE RATING
RESET TYPE: AUTOMATIC OR MANUAL
OPERATING FREQUENCY: 60 Hz
TYPE: CLASS A
GROUND TRIP CURRENT: 4-6 mA
OVERLOAD CURRENT: 90 AMP 125 VAC
INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE
ENDURANCE OPERATIONS: 3000 OPERATIONS

MATERIAL NO.	ENGINEERING NO.	LENGTH "L"	POWER-UP
1301530091	15054-1A	2 FT ± 1 IN	AUTO
1301530095	15054-25A	25 FT ± 2 IN	AUTO
1301530092	15054-1M	2 FT ± 1 IN	MANUAL
1301530096	15054-25M	25 FT ± 2 IN	MANUAL

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION											
FUNCTIONAL SYMBOLS		DIMENSION UNITS		SCALE		CURRENT REV DESC: MIGRATION TO ECTR/NX					
= 0		INCH		NTS		<p>molex</p> <p>120V 15A GFCI PLUG W/ MOLDED CONNECTOR NEMA 5-15</p> <p>PRODUCT CUSTOMER DRAWING</p> <p>DOCUMENT NUMBER: SD-130153-017 DOC TYPE: PSD DOC PART: 001 REVISION: A1</p> <p>EC NO: 684571 DRWN: VBASUTHKARP 2021/11/06 CHKD: DNGUYEN62 2022/01/20 APPR: HKNEELAND 2022/02/02</p> <p>INITIAL REVISION: DRWN: HRUIZ01 2013/02/07 APPR: JFMURPHY 2015/04/20</p> <p>DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS</p> <p>THIRD ANGLE PROJECTION</p> <p>DRAWING: B-SIZE SERIES: 130153</p> <p>MATERIAL NUMBER: SEE TABLE CUSTOMER: GENERAL MARKET SHEET NUMBER: 1 OF 1</p>					
= 0		GENERAL TOLERANCES (UNLESS SPECIFIED)									
= 0		ANGULAR TOL ± 0.5°									
DIVISIONAL SYMBOLS		4 PLACES ±									
		3 PLACES ±									
		2 PLACES ± 0.13									
		1 PLACE ± 0.25									
		0 PLACES ±									