

**SN54ALS845, SN54AS845, SN54ALS846, SN54AS846
SN74ALS845, SN74AS845, SN74ALS846, SN74AS846
8-BIT BUS INTERFACE D-TYPE LATCHES WITH 3-STATE OUTPUTS**

D2825, DECEMBER 1983—REVISED APRIL 1986

- 3-State Buffer-Type Outputs Drive Bus-Lines Directly
- Bus-Structured Pinout
- Provides Extra Bus Driving Latches Necessary for Wider Address/Data Paths or Buses with Parity
- Buffered Control Inputs to Reduce DC Loading
- Power-Up High-Impedance State
- Package Options Include Plastic "Small Outline" Packages, Both Plastic and Ceramic Chlp Carriers, and Standard Plastic and Ceramic 300-mil DIPs
- Dependable Texas Instruments Quality and Reliability


description

These 8-bit latches feature three-state outputs designed specifically for driving highly capacitive or relatively low-impedance loads. They are particularly suitable for implementing buffer registers, I/O ports, bidirectional bus drivers, and working registers.


The eight latches are transparent D-type. The 'ALS845 and 'AS845 have noninverting data (D) inputs. The 'ALS846 and 'AS846 have inverting D inputs. Since CLR and PRE are independent of the clock, taking the CLR input low will cause the eight Q outputs to go low. Taking the PRE input low will cause the eight Q outputs to go high. When both PRE and CLR are taken low, the outputs will follow the preset condition.

The buffered output control inputs (OC1, OC2, and OC3) can be used to place the eight outputs in either a normal logic state (high or low levels) or a high-impedance state. In the high-impedance state, the outputs neither load nor drive the bus lines significantly. The high-impedance state and increased drive provide the capability to drive the bus lines in a bus-organized system without need for interface or pull-up components. The output controls do not affect the internal operation of the latches. Old data can be retained or new data can be entered while the outputs are in the high-impedance state.


SN54ALS845, SN54AS845 . . . JT PACKAGE
SN74ALS845, SN74AS845 . . . DW OR NT PACKAGE




SN54ALS846, SN54AS846 . . . FK PACKAGE
SN74ALS846, SN74AS846 . . . FN PACKAGE



SN54ALS846, SN54AS846 . . . JT PACKAGE
SN74ALS846, SN74AS846 . . . DW OR NT PACKAGE



SN54ALS846, SN54AS846 . . . FK PACKAGE
SN74ALS846, SN74AS846 . . . FN PACKAGE



NC—No internal connection

2
ALS and AS Circuits

2945 6-14

PRODUCTION DATA documents contain information current as of publication date. Products conform to these specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.



POST OFFICE BOX 655012 • DALLAS, TEXAS 75265

Copyright © 1983, Texas Instruments Incorporated

2-671

T-52-09

**SN54ALS845, SN54AS845, SN54ALS846, SN54AS846
SN74ALS845, SN74AS845, SN74ALS846, SN74AS846
8-BIT BUS INTERFACE D-TYPE LATCHES WITH 3-STATE OUTPUTS**

The -1 versions of the SN74ALS845 and SN74ALS846 parts are identical to the standard versions except that the recommended maximum IOL is increased to 48 milliamperes. There are no -1 versions of the SN54ALS845 and SN54ALS846.

The SN54ALS845, SN54AS845, SN54ALS846, and SN54AS846 are characterized for operation over the full military temperature range of -55°C to 125°C. The SN74ALS845, SN74AS845, SN74ALS846, and SN74AS846 are characterized for operation from 0°C to 70°C.

FUNCTION TABLES

'ALS845, 'AS845


INPUTS								OUTPUT
PRE	CLR	OC1	OC2	OC3	C	D	Q	
L	H	L	L	L	X	X	H	
H	L	L	L	L	X	X	L	
L	L	L	L	L	X	X	H	
H	H	L	L	L	H	L	L	
H	H	L	L	L	H	H	H	
H	H	L	L	L	L	X	Q ₀	
X	X	X	X	H	X	X	Z	
X	X	X	H	X	X	X	Z	
X	X	H	X	X	X	X	Z	

'ALS846, 'AS846


INPUTS								OUTPUT
PRE	CLR	OC1	OC2	OC3	C	D	Q	
L	H	L	L	L	X	X	H	
H	L	L	L	L	X	X	L	
L	L	L	L	L	X	X	H	
H	H	L	L	L	H	L	H	
H	H	L	L	L	H	H	L	
H	H	L	L	L	L	X	Q ₀	
X	X	X	X	H	X	X	Z	
X	X	X	H	X	X	X	Z	
X	X	H	X	X	X	X	Z	

logic symbols†

'ALS845, 'AS845



'ALS846, 'AS846



† These symbols are in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12. Pin numbers shown are for DW, JT, and NT packages.

2 ALS and AS Circuits



**SN54ALS845, SN54AS845, SN54ALS846, SN54AS846
SN74ALS845, SN74AS845, SN74ALS846, SN74AS846
8-BIT BUS INTERFACE D-TYPE LATCHES WITH 3-STATE OUTPUTS**

logic diagrams (positive logic)

T-52.09

'ALS845, 'AS845

'ALS846, 'AS846



Pin numbers shown are for DW, JT, and NT packages.

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, VCC	7 V
Input voltage	7 V
Voltage applied to a disabled 3-state output	5.5 V
Operating free-air temperature range:	
SN54ALS845, SN54AS845, SN54ALS846, SN54AS846	-55 °C to 125 °C
SN74ALS845, SN74AS845, SN74ALS846, SN74AS846	-0 °C to 70 °C
Storage temperature range	-65 °C to 150 °C

2

ALS and AS Circuits

T-52.09

SN54ALS845, SN74ALS845
8-BIT BUS INTERFACE D-TYPE LATCHES WITH 3-STATE OUTPUTS

recommended operating conditions

	SN54ALS845			SN74ALS845			UNIT	
	MIN	NOM	MAX	MIN	NOM	MAX		
V _{CC} Supply voltage	4.5	5	5.5	4.5	5	5.5	V	
V _{IH} High-level input voltage	2			2			V	
V _{IL} Low-level input voltage			0.7			0.8	V	
I _{OH} High-level output current			-1			-2.6	mA	
I _{OL} Low-level output current			12			24	mA	
						48 [†]		
t _w Pulse duration	CLR or PRE low		40			35	ns	
	C high		25			20		
t _{su} Setup time, data before enable C _I			16			10	ns	
t _h Hold time, data after enable C _I			7			5	ns	
T _A Operating free-air temperature			-65	125		0	70	°C

[†]The extended limit applies only if V_{CC} is maintained between 4.75 V and 5.25 V. The 48 mA limit applies for SN74ALS845-1 only.

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	SN54ALS845			SN74ALS845			UNIT
		MIN	TYP [‡]	MAX	MIN	TYP [‡]	MAX	
V _{IK}	V _{CC} = 4.5 V, I _I = -18 mA			-1.2			-1.2	V
V _{OH}	V _{CC} = 4.5 V to 6.5 V, I _{OH} = -0.4 mA	V _{CC} -2			V _{CC} -2			V
	V _{CC} = 4.5 V, I _{OH} = -1 mA	2.4	3.3					
	V _{CC} = 4.5 V, I _{OH} = -2.6 mA				2.4	3.2		
V _{OL}	V _{CC} = 4.5 V, I _{OL} = 12 mA		0.25	0.4		0.25	0.4	V
	V _{CC} = 4.5 V, I _{OL} = 24 mA					0.35	0.5	
	(I _{OL} = 48 mA for -1 versions)							
I _{OZH}	V _{CC} = 5.5 V, V _O = 2.7 V			20			20	μA
I _{OZL}	V _{CC} = 5.5 V, V _O = 0.4 V			-20			-20	μA
I _I	V _{CC} = 5.5 V, V _I = 7 V			0.1			0.1	mA
I _{IH}	V _{CC} = 5.5 V, V _I = 2.7 V			20			20	μA
I _{IL}	V _{CC} = 5.5 V, V _I = 0.4 V			-0.1			-0.1	mA
I _{O^s}	V _{CC} = 5.5 V, V _O = 2.25 V	-30		-112	-30		-112	mA
I _{CC}	V _{CC} = 5.5 V	Outputs high	21	36	21	36	mA	
		Outputs low	41	67	41	67		
		Outputs disabled	25	42	25	42		

[‡]All typical values are at V_{CC} = 5 V, T_A = 25 °C.

[§]The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, I_{O^s}.

2

ALS and AS Circuits

SN54ALS845, SN74ALS845
8-BIT BUS INTERFACE D-TYPE LATCHES WITH 3-STATE OUTPUTS

T-52.09

switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC} = 5 V, C _L = 50 pF, R ₁ = 500 Ω, R ₂ = 500 Ω, T _A = 25 °C			V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R ₁ = 500 Ω, R ₂ = 500 Ω, T _A = MIN to MAX			UNIT	
			'ALS845			SN64ALS845		SN74ALS845		
			MIN	TYP	MAX	MIN	MAX	MIN		MAX
t _{PLH}	D	Q	7	11	2	15	2	13	ns	
t _{PHL}			11	15	4	20	4	18		
t _{PLH}	C	Q	12	18	5	25	5	21	ns	
t _{PHL}			16	23	8	30	8	26		
t _{PLH}	PRE	Q	13	19	5	25	6	22	ns	
t _{PHL}			19	26	4	35	6	30		
t _{PLH}	CLR	Q	19	26	4	35	6	30	ns	
t _{PHL}			16	22	6	28	6	24		
t _{PZH}	OC	Q	9	14	2	18	3	16	ns	
t _{PZL}			12	17	4	20	5	18		
t _{PHZ}	OC	Q	4	9	1	12	1	11	ns	
t _{PLZ}			6	11	2	14	2	12		

NOTE 1: Load circuit and voltage waveforms are shown in Section 1.

2

ALS and AS Circuits

SN54ALS846, SN74ALS846
8-BIT BUS INTERFACE D-TYPE LATCHES WITH 3-STATE OUTPUTS

T-52-09

recommended operating conditions

	SN54ALS846			SN74ALS846			UNIT
	MIN	NOM	MAX	MIN	NOM	MAX	
V _{CC} Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V _{IH} High-level input voltage	2			2			V
V _{IL} Low-level input voltage			0.7			0.8	V
I _{OH} High-level output current			-1			-2.6	mA
I _{OL} Low-level output current			12			24	mA
						48†	
t _w Pulse duration	CLR or PRE low		40	35			ns
	C high		25	20			
t _{su} Setup time, data before enable C↓			16	10			ns
t _h Hold time, data after enable C↓			7	5			ns
T _A Operating free-air temperature			-55	125		0	70 °C

† The extended limit applies only if V_{CC} is maintained between 4.75 V and 5.25 V. The 48 mA limit applies for SN74ALS846-1 only.

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	SN54ALS846		SN74ALS846		UNIT		
		MIN	TYP‡	MAX	MIN		TYP‡	MAX
V _{IK}	V _{CC} = 4.5 V, I _I = -18 mA			-1.2		-1.2	V	
V _{OH}	V _{CC} = 4.5 V to 5.5 V, I _{OH} = -0.4 mA	V _{CC} -2		V _{CC} -2			V	
	V _{CC} = 4.5 V, I _{OH} = -1 mA	2.4	3.3					
	V _{CC} = 4.5 V, I _{OH} = -2.6 mA			2.4	3.2			
V _{OL}	V _{CC} = 4.5 V, I _{OL} = 12 mA		0.25	0.4			V	
	V _{CC} = 4.5 V, I _{OL} = 24 mA				0.35	0.5		
	(I _{OL} = 48 mA for -1 versions)							
I _{OZH}	V _{CC} = 5.5 V, V _O = 2.7 V		20		20		μA	
I _{OZL}	V _{CC} = 5.5 V, V _O = 0.4 V		-20		-20		μA	
I _I	V _{CC} = 5.5 V, V _I = 7 V		0.1		0.1		mA	
I _{IH}	V _{CC} = 5.5 V, V _I = 2.7 V		20		20		μA	
I _{IL}	V _{CC} = 5.5 V, V _I = 0.4 V		-0.1		-0.1		mA	
I _O §	V _{CC} = 6.5 V, V _O = 2.25 V	-30		-112	-30		-112	mA
I _{CC}	V _{CC} = 5.5 V	Outputs high	22	36	22	36	mA	
		Outputs low	43	72	43	72		
		Outputs disabled	28	48	28	48		

‡ All typical values are at V_{CC} = 5 V, T_A = 25°C.§ The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, I_{OS}.

SN54ALS846, SN74ALS846
8-BIT BUS INTERFACE D-TYPE LATCHES WITH 3-STATE OUTPUTS

T-52.09

switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	VCC = 5 V, CL = 50 pF, R1 = 500 Ω, R2 = 500 Ω, TA = 25 °C			VCC = 4.5 V to 5.5 V, CL = 50 pF, R1 = 500 Ω, R2 = 500 Ω, TA = MIN to MAX			UNIT	
			ALS846			SN54ALS846		SN74ALS846		
			MIN	TYP	MAX	MIN	MAX	MIN		MAX
tPLH	D	Q	11	16	4	22	4	20	ns	
tPHL			9	13	3	17	3	15		
tPLH	C	Q	17	23	8	31	8	27	ns	
tPHL			14	19	6	26	6	22		
tPLH	PRE	Q	13	17	6	24	5	20	ns	
tPHL			18	24	9	36	9	26		
tPLH	CLR	Q	14	19	6	23	6	21	ns	
tPHL			16	21	9	25	9	23		
tPZH	OC	Q	10	13	3	17	3	15	ns	
tPZL			13	17	5	20	5	18		
tPHZ	OC	Q	7	10	1	12	1	11	ns	
tPLZ			7	11	2	14	2	12		

NOTE 1: Load circuit and voltage waveforms are shown in Section 1.

2
ALS and AS Circuits

SN54AS845, SN54AS846
SN74AS845, SN74AS846
8-BIT BUS INTERFACE D-TYPE LATCHES WITH 3-STATE OUTPUTS

T-52.09

recommended operating conditions

		SN54AS845 SN54AS846			SN74AS845 SN74AS846			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V _{CC}	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V _{IH}	High-level input voltage	2			2			V
V _{IL}	Low-level input voltage	0.8			0.8			V
I _{OH}	High-level output current	-24			-24			mA
I _{OL}	Low-level output current	32			48			mA
t _w	Pulse duration	CLR or PRE low		5	4		ns	
		C high		5	4			
t _{su}	Setup time, data before enable C _I	3.5			2.5			ns
t _h	Hold time, data after enable C _I	3.5			2.5			ns
t _r	Recovery time	PRE		17	15		ns	
		CLR		16	14			
T _A	Operating free-air temperature	-55		125	0		70	°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	SN54AS845 SN54AS846		SN74AS845 SN74AS846		UNIT	
		MIN	TYP†	MAX	MIN		TYP†
V _{IK}	V _{CC} = 4.5 V, I _I = -18 mA	-1.2		-1.2		V	
V _{OH}	V _{CC} = 4.5 V, I _{OH} = -2 mA	V _{CC} -2		V _{CC} -2		V	
	V _{CC} = 4.5 V, I _{OH} = -15 mA	2.4	3.2	2.4	3.2		
	V _{CC} = 4.5 V, I _{OH} = -24 mA	2		2			
V _{OL}	V _{CC} = 4.5 V, I _{OL} = 32 mA	0.25 0.5				V	
	V _{CC} = 4.5 V, I _{OL} = 48 mA			0.35	0.5		
I _{OZH}	V _{CC} = 5.5 V, V _O = 2.7 V	50		50		μA	
I _{OZL}	V _{CC} = 5.5 V, V _O = 0.4 V	-50		-50		μA	
I _I	V _{CC} = 5.5 V, V _I = 7 V	0.1		0.1		mA	
I _{IH}	V _{CC} = 5.5 V, V _I = 2.7 V	20		20		μA	
I _{IL}	V _{CC} = 5.5 V, V _I = 0.4 V	-0.5		-0.5		mA	
I _O ‡	V _{CC} = 5.5 V, V _O = 2.25 V	-30	-112	-30	-112	mA	
I _{CC}	V _{CC} = 5.5 V		Outputs high		35	58	mA
			Outputs low		52	85	
			Outputs disabled		52	85	
			Outputs high		36	59	
			Outputs low		53	87	
			Outputs disabled		53	87	

†All typical values are at V_{CC} = 5 V, T_A = 25°C.

‡The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, I_{OS}.

2 ALS and AS Circuits

**SN54AS845, SN54AS846
SN74AS845, SN74AS846**

8-BIT BUS INTERFACE D-TYPE LATCHES WITH 3-STATE OUTPUTS

7-52-09

'AS845 switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	VCC = 4.5 V to 6.5 V, CL = 50 pF, R1 = 500 Ω, R2 = 500 Ω, TA = MIN to MAX				UNIT
			SN54AS845		SN74AS845		
			MIN	MAX	MIN	MAX	
tPLH	D	Q	1	8.5	1	6.5	ns
tPHL			1	10	1	9	
tPLH	C	Q	2	13	2	12	ns
tPHL			2	13	2	12	
tPLH	PRE	Q	2	12	2	10	ns
tPHL	CLR	Q	2	14	2	13	ns
tPHL	OC	Q	2	13.5	2	10.5	ns
tPZL			2	15	2	13.5	
tPHZ	OC	Q	1	10	1	8	ns
tPLZ			1	10	1	8	

'AS846 switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	VCC = 4.5 V to 6.5 V, CL = 50 pF, R1 = 500 Ω, R2 = 500 Ω, TA = MIN to MAX				UNIT
			SN54AS846		SN74AS846		
			MIN	MAX	MIN	MAX	
tPLH	D	Q	1	11	1	8.5	ns
tPHL			1	11	1	10	
tPLH	C	Q	2	14	2	12.5	ns
tPHL			2	14	2	13	
tPLH	PRE	Q	2	12	2	10	ns
tPHL	CLR	Q	2	14.5	2	13.5	ns
tPHL	OC	Q	2	14.5	2	12	ns
tPZL			2	15	2	13.5	
tPHZ	OC	Q	1	10	1	8	ns
tPLZ			1	10	1	8	

NOTE 1: Load circuit and voltage waveforms are shown in Section 1.

2
ALS and AS Circuits