

YASMEEN-50-W-C-WHT

~36° spot beam. Assembly with holder C compatible with LEDiL HEKLA. White version.

SPECIFICATION:

| | |
|----------------|-----------|
| Dimensions | Ø 49.9 mm |
| Height | 28.1 mm |
| ROHS compliant | yes ⓘ |




MATERIALS:

| Component | Type | Material | Colour | Finish |
|----------------------|-------------|----------|--------|--------|
| YASMEEN-50-W | Single lens | PMMA | clear | |
| YASMEEN-50-HLD-C-WHT | Holder | PC | white | |













ORDERING INFORMATION:

| Component | Type | Qty in box | MOQ | MPQ | Box weight (kg) |
|--------------------------------|-------------|------------|-----|-----|-----------------|
| CP17566_YASMEEN-50-W-C-WHT | Single lens | 252 | 112 | 28 | 9.2 |
| » Box size: 476 x 273 x 305 mm | | | | | |














See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):

| | | |
|--|--|---|
| <p></p> <p>LED V11 HD Gen 8</p> <p>FWHM / FWTM 32.0° / 56.0°</p> <p>Efficiency 93 %</p> <p>Peak intensity 2.5 cd/m</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components: Bender Wirth: 633d Hekla</p> |  |  |
| <p></p> <p>LED V4 HD Gen 7</p> <p>FWHM / FWTM 34.0° / 52.0°</p> <p>Efficiency 88 %</p> <p>Peak intensity 2.4 cd/m</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components: F15253_HEKLA-SOCKET-A</p> |  |  |
| <p></p> <p>LED V6 HD Gen 7</p> <p>FWHM / FWTM 34.0° / 53.0°</p> <p>Efficiency 87 %</p> <p>Peak intensity 2.4 cd/m</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components: F15255_HEKLA-SOCKET-C</p> |  |  |
| <p></p> <p>LED VERO10</p> <p>FWHM / FWTM 33.0° / 56.0°</p> <p>Efficiency 86 %</p> <p>Peak intensity 2.3 cd/m</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components: F15616_HEKLA-SOCKET-F</p> |  |  |



OPTICAL RESULTS (MEASURED):

| | | |
|--|--|---|
| <p></p> <p>LED Vesta DTW 13mm (21W) FWHM / FWTM 36.0° / 62.0° Efficiency 90 % Peak intensity 2 cd/m LEDs/each optic 1 Light colour Tunable White Required components: Bender Wirth: 632b Hekla XL</p> |  |  |
| <p></p> <p>LED Vesta DTW 15mm (33W) FWHM / FWTM 38.0° / 65.0° Efficiency 89 % Peak intensity 1.7 cd/m LEDs/each optic 1 Light colour Tunable White Required components: Bender Wirth: 632b Hekla XL</p> |  |  |
| <p></p> <p>LED Vesta DTW 9mm (4W/6W/12W) FWHM / FWTM 32.0° / 55.0° Efficiency 93 % Peak intensity 2.6 cd/m LEDs/each optic 1 Light colour White Required components: Bender Wirth: 652b Hekla</p> |  |  |
| <p>CITIZEN</p> <p>LED CLL02x/CLU02x (LES10) FWHM / FWTM 33.0° / 56.0° Efficiency 86 % Peak intensity 2.3 cd/m LEDs/each optic 1 Light colour White Required components: F17435_HEKLA-G2-C</p> |  |  |

OPTICAL RESULTS (MEASURED):



CITIZEN

LED CLU700/701/702/703
FWHM / FWTM 34.0° / 53.0°
Efficiency 87 %
Peak intensity 2.4 cd/m
LEDs/each optic 1
Light colour White
Required components:
F17435_HEKLA-G2-C





CITIZEN

LED CLU7A2/7A3
FWHM / FWTM 35.0° / 52.0°
Efficiency 88 %
Peak intensity 2.4 cd/m
LEDs/each optic 1
Light colour White
Required components:
F17435_HEKLA-G2-C




CITIZEN

LED CLU7B2
FWHM / FWTM 34.0° / 51.0°
Efficiency 88 %
Peak intensity 2.4 cd/m
LEDs/each optic 1
Light colour White
Required components:
F17435_HEKLA-G2-C



CREE LED



LED CMA1516
FWHM / FWTM 33.0° / 55.0°
Efficiency 87 %
Peak intensity 2.4 cd/m
LEDs/each optic 1
Light colour White
Required components:
F17436_HEKLA-G2-D



OPTICAL RESULTS (MEASURED):


CREE LED

LED CMT14xx
 FWHM / FWTM 33.0° / 56.0°
 Efficiency 86 %
 Peak intensity 2.3 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:
 F17435_HEKLA-G2-C





CREE LED

LED CXA/B 13xx
 FWHM / FWTM 34.0° / 53.0°
 Efficiency 89 %
 Peak intensity 2.4 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:
 F17439_HEKLA-G2-J





CREE LED

LED CXA/B 15xx
 FWHM / FWTM 33.0° / 55.0°
 Efficiency 87 %
 Peak intensity 2.4 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:
 F17436_HEKLA-G2-D



LUMILEDS



LED LUXEON CoB 1202/1203
 FWHM / FWTM 32.5° / 54.5°
 Efficiency 86 %
 Peak intensity 2.4 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:
 F17437_HEKLA-G2-H



OPTICAL RESULTS (MEASURED):



LUMILEDS

LED LUXEON CoB 1204HD
 FWHM / FWTM 32.0° / 54.0°
 Efficiency 87 %
 Peak intensity 2.4 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:
 F17437_HEKLA-G2-H





LUMILEDS

LED LUXEON CoB M02/M03
 FWHM / FWTM 33.0° / 54.0°
 Efficiency 87 %
 Peak intensity 2.4 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:
 F17436_HEKLA-G2-D





LUMILEDS

LED LUXEON CoB S01
 FWHM / FWTM 34.0° / 52.0°
 Efficiency 88 %
 Peak intensity 2.4 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:
 F17439_HEKLA-G2-J



LUMINUS



LED CXM-3
 FWHM / FWTM 34.0° / 50.0°
 Efficiency 87 %
 Peak intensity 2.4 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:
 F17435_HEKLA-G2-C





OPTICAL RESULTS (MEASURED):




LED CXM-4
 FWHM / FWTM 34.0° / 51.0°
 Efficiency 88 %
 Peak intensity 2.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 F17435_HEKLA-G2-C





LED COB L-Type (LES 9)
 FWHM / FWTM 33.0° / 54.0°
 Efficiency 86 %
 Peak intensity 2.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 F17437_HEKLA-G2-H



LED COB S-Type (LES 7)
 FWHM / FWTM 34.0° / 54.0°
 Efficiency 87 %
 Peak intensity 2.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 F15848_HEKLA-SOCKET-G




LED Fortimo SLM L09 CoB
 FWHM / FWTM 32.0° / 54.0°
 Efficiency 86 %
 Peak intensity 2.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 F17437_HEKLA-G2-H




OPTICAL RESULTS (MEASURED):

SAMSUNG



LED LC003D / LC006D / LC009D / LC013D
 FWHM / FWTM 33.0° / 56.0°
 Efficiency 86 %
 Peak intensity 2.3 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:
 F17435_HEKLA-G2-C



LED MJT COB LES 6
 FWHM / FWTM 35.0° / 54.0°
 Efficiency 88 %
 Peak intensity 2.3 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:
 F17435_HEKLA-G2-C





LED MJT COB LES 9.8
 FWHM / FWTM 33.0° / 56.0°
 Efficiency 86 %
 Peak intensity 2.3 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:
 F17435_HEKLA-G2-C



TRIDONIC

LED SLE G7 LES09
 FWHM / FWTM 33.0° / 55.0°
 Efficiency 87 %
 Peak intensity 2.4 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:
 F17435_HEKLA-G2-C



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)