ATGBICS FTLF8529P5BCV Finisar Compatible Transceiver SFP+ 16G Fibre Channel-SW (850nm, MMF, 100m, DOM)

Brand : ATGBICS Product code: FTLF8529P5BCV-C

Product name : FTLF8529P5BCV Finisar Compatible Transceiver SFP+ 16G Fibre Channel-SW (850nm, MMF,

100m, DOM)

A COLD COMMUNICATION OF THE PARTY OF THE PAR

FTLF8529P5BCV Finisar Compatible Transceiver SFP+ 16G Fibre Channel-SW (850nm, MMF, 100m, DOM)

ATGBICS FTLF8529P5BCV Finisar Compatible Transceiver SFP+ 16G Fibre Channel-SW (850nm, MMF, 100m, DOM):

ATGBICS FTLF8529P5BCV 16GBase-SR Short Wave fibre Channel supports a distance of up to 100m over multi-mode fibre (MMF) using a wavelength of 850nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of Finisar FTLF8529P5BCV= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Features	
SFP transceiver type * Fiber optic Maximum data transfer rate * 16000 Mbit/s Interface type * SFP+ Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported Fiber optic connector SFP transceiver standard Maximum transfer distance Wavelength Ethernet LAN Ethernet interface type Digital Diagnostics Monitoring	16000 Mbit/s	Certification	CE, FCC, RoHS
		Power	
	× ✓ LC	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
	Operational conditions Maximum operating temperature Operating temperature (T-T)	70 °C 0 - 70 °C	
	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-40 - 85 °C 0 - 95% 0 - 95%	
(DDM) Wavelength-division multiplexing (WDM)	×	Weight & dimensions Width	13.4 mm
Features Product colour	Silver	Depth Height	56.5 mm 8.5 mm
Housing material Metal Plug and Play Hot-Plug support Hot-swap		Weight Packaging data	19 g
	*	Number of products included Package type	1 pc(s) Box
Easy to install	√ China Finisar	Technical details	
Country of origin Brand compatibility		Sustainability compliance Sustainability certificates Doesn't contain	RoHS Lead



5056468770950

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.