



Specifications

Current Rating: 3Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding: 600VAC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -40°C to +105°C

Materials

Contact Material: Brass
 Insulator Material: Polyester, UL 94V-0
 Nylon 6T
 Contact plating: 30U' Gold

All materials must be GP materials

| NUMBER OF POSITION | Dimensions | |
|--------------------|------------|-------|
| | A | B |
| 10 | 20.32 | 12.70 |
| 14 | 25.40 | 17.78 |
| 16 | 27.94 | 20.32 |
| 20 | 33.02 | 25.40 |
| 26 | 40.64 | 33.02 |
| 30 | 45.72 | 38.10 |
| 34 | 50.80 | 43.18 |
| 40 | 58.42 | 50.80 |
| 50 | 71.12 | 63.50 |
| 60 | 83.82 | 76.20 |
| 64 | 88.90 | 81.28 |

CnC Tech, LLC
 Industrial Cable and Connector Technology

| | | | |
|----------------------|----------|-----------------|--|
| DESIGN <i>lumayl</i> | PART NO. | 3020-XX-0100-02 | |
| DATE 2011. 12. 05 | REV A | SIZE A4 | UNLESS OTHERWISE SPECIFIED TOLERANCE ANG ±5° 0 ±0.3 .0 ±0.15 .00 ±0.10 |
| CHECKED | UNIT mm | | |