48 INCHES LENGTH



Connector A 132453 SMA Jack Straight Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm LMR-240 Continuity/Hi-Pot Connector B 132451 SMA Plug Straight Brass Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Connector A			Cable			Connector B		
Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material Contact Finish:	Part #:132453Description:SMA BHD JK LMR240 Optimized 50Type:SMAGender:JackBody Type:StraightContact Type:SolderPolarity:Standardmpedance:50 OhmMounting:Bulkhead - Rear MountBody Material:BrassBody Finish:GoldP Rating:NoneContact Material:Beryllium Copper		Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	Cable LMR-240 LMR-240 - FEP 0.24 FEP Braid 0.24 50 Ohm None Continuity Hi-Pot 48 Inches	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish:	132451 SMA PLUG LMR240 Optimized 50O SMA Plug Straight Solder Standard 50 Ohm Cable Brass Gold None I: Brass		
Max. Freq.: Booting:	6 GHz SMA Jack Straight BHD				Max. Freq.: Booting: Clocking:	6 GHz SMA Plug Straight 0°		
Amphenol CUSTOM CABLE CONTROLLED DOCUMENT - DO NOT COPY		THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.		BLE ED DF ING Part No:	SMA-ST-JK/SMA-ST-PL LMR24 481		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	



RoHS 2015/863 Compliance Statement

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/2/2023

Part Number: Q-3203G000M048I

Manufacturer: Amphenol Custom Cable

Description: SMA-ST-JK/SMA-ST-PL LMR24 48I

This information is valid as of the date indicated for the item (part number) listed.

Director of Quality Assurance

Janice Frank