

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	SQUARE NUT PART INFORMATION ADDED	13APR2018	RK	PS

NOTES:

- MATERIALS AND FINISH:  
HOUSING: HIGH TEMPERATURE POLYAMIDE, UL94V-0,  
COLOR: BLACK.  
TERMINAL: PHOSPHOR BRONZE, TIN PLATED.  
SQUARE NUT: BRASS, NICKEL PLATED.
- MECHANICAL  
MAX. INSERTION FORCE PER POLE : 3.0 N  
MIN. WITHDRAWAL FORCE PER POLE : 1.5 N  
MIN. PC BOARD HOLES DIAMETER : 1.2 mm  
MAX. PC BOARD THICKNESS : 2.4 mm
- ELECTRICAL  
WIRE RANGE : 14-30 AWG  
MAX. VOLTAGE : 300 V  
MAX CURRENT : 11 A  
CONTACT RESISTANCE : <15 m Ohm  
INSULATION RESISTANCE : >1000 M Ohm (500V DC)
- OPERATING TEMPERATURE RANGE: -40°C TO +110°C
- CONNECTOR ASSEMBLY INCLUDED 2 SQUARE NUTS LOADED IN CAVITY.

Dimensions: 3.81±0.05, 2.6 REF, 7.25±0.15, 3.0

Features: POLARIZATION KEY SLOT, CAVITY FOR M2.5 FIXING SCREW 2 PLC

Dimensions: DIM A, 0.80±0.02

Dimensions: 7.25, 9.2±0.2, 3.4±0.2, 0.80±0.02, 3.0

Labels: SQUARE NUT, HOUSING, TERMINAL

Note: 6 NOT CUMULATIVE TOLERANCE.

56.11	12	1-1776133-2
52.30	11	1-1776133-1
48.49	10	1-1776133-0
44.68	9	1776133-9
40.87	8	1776133-8
37.06	7	1776133-7
33.25	6	1776133-6
29.44	5	1776133-5
25.63	4	1776133-4
21.82	3	1776133-3
18.01	2	1776133-2
DIM A	NO OF POS.	PART NUMBER

Dimensions: 3.81,  $\phi 1.2^{+0.1}_0$ ,  $\phi 0.1$

RECOMMENDED PC BOARD LAYOUT

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN S. SCHLEGEL 06JAN2010

CHK C RICHARD 06JAN2010

APVD C RICHARD 06JAN2010

PRODUCT SPEC

APPLICATION SPEC

WEIGHT -

CUSTOMER DRAWING

DIMENSIONS:  
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±
1 PLC	±0.3
2 PLC	±0.25
3 PLC	±
4 PLC	±
ANGLES	±2°

MATERIAL  
SEE NOTESFINISH  
SEE NOTES

NAME: TERMINAL BLOCK HEADER ASSEMBLY, STRAIGHT, W/ THREADED FLANGE, 3.81mm PITCH

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C-1776133	-

SCALE	SHEET	OF	REV
3:1	1	1	A

TE Connectivity

1470-19 (3/13)