

**MODEL:** CEP-1172 | **DESCRIPTION:** PIEZO BUZZER TRANSDUCER**FEATURES**

- feedback pin
- 12 Vdc rating
- 3.3 kHz rated frequency


**SPECIFICATIONS**

parameter	conditions/description	min	typ	max	units
rated voltage			12		Vdc
operating voltage		3		28	Vdc
current consumption	at rated voltage			7	mA
rated frequency		2,800	3,300	3,800	Hz
sound pressure level	at 30 cm, rated voltage	81			dB
dimensions	∅31.4 x 16.0				mm
weight				6.7	g
material	ABS UL94 1/16" HB High Heat (black)				
terminal	solder pins				
operating temperature		-30		85	°C
storage temperature		-40		95	°C
RoHS	yes				

Notes: 1. All specifications measured at 5-35°C, humidity at 45-85%, under 86-106kPa pressure, unless otherwise noted.

**SOLDERABILITY**


parameter	conditions/description	min	typ	max	units
wave soldering	see recommended wave soldering profile			250	°C





## MECHANICAL DRAWING

units: mm  
tolerance: ±0.5 mm


PIN CONNECTIONS	
Pin	Function
M	+terminal
G	-terminal
F	feedback



## PERFORMANCE CURVES



## DRIVING CIRCUIT



Notes: 1. The current consumption and the sound pressure level are measured by using the recommended driving circuit shown above.

## REVISION HISTORY

rev.	description	date
1.0	initial release	06/25/2007
1.01	brand update	05/06/2020
1.02	logo, datasheet style update	08/05/2022

The revision history provided is for informational purposes only and is believed to be accurate.



CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[cuidevices.com](http://cuidevices.com)