TRIPP-LITE

Heavy-Duty USB-A to Lightning Sync/Charge Cable, MFi Certified - M/M, USB 2.0, 10 ft. (3.05 m)

MODEL NUMBER: M100-010-HD



Durable Lightning cable with bulletproof Aramid fiber construction charges and syncs your Apple iPhone, iPad or iPod via computer or USB charger.

Features

Reinforced Cable Charges and Syncs Your Latest-Generation iPhone, iPad and iPodThis heavyduty USB sync/charge cable (M/M) connects your latest-generation iPhone, iPad or iPod to the USB-A port on your computer or USB wall charger, so you can charge your Apple device and transfer data at the same time. Plus, the M100-010-HD is specially designed using bulletproof Aramid fiber to stand up to the strain of daily use.

Constructed Using Bulletproof Aramid Fiber for Long LifeCharging cables used with mobile devices are often pulled, strained and generally abused, sometimes to the point of failure. To counter day-to-day abuse, the super-robust M100-010-HD is constructed using bulletproof Aramid fiber to reinforce the conductors inside the cable. The double-braided nylon jacket helps maintain top performance and long life, while the enhanced bulletproof Aramid protection stands up to the strain of rigorous and frequent use. Integral strain relief gives the cable extra flexibility, reduces stress, and helps the cable move freely without cracking or breaking loose from the connector.

MFi-Certified for Broad Device CompatibilityThe 10-ft. (3.05 m) 5V 2.4A (12W) Lightning cable is MFicertified for use with the latest generation of iPhone, iPad and iPod devices. The USB-A plug connects to any computer or wall charger with a USB port.

Reversible Lightning Plug Connects in Either DirectionConnect the reversible 8-pin Lightning plug to your Apple device for charging and synchronizing. The fumble-free plug connects in either direction to ensure fast, easy connection every time.

Specifications

OVERVIEW	
UPC Code	037332239471
Technology	Lightning; USB 2.0 (High Speed)

Highlights

- Engineered using bulletproof Aramid fiber to stand up to frequent and rigorous use
- Charges your device and transfers data through your computer or USB wall charger
- MFi-certified for broad compatibility with your Apple iPhone, iPad or iPod
- Integral strain relief helps cable move freely without stress or cracking
- Reversible Lightning plug connects in either direction for immediate no-fuss use

Applications

- Charge and sync your Apple iPhone, iPad or iPod using the USB-A port on your computer or a wall charger up to 10-ft. (3.05 m) away
- Transfer photos and other important files between an external hard drive and your Apple device

System Requirements

- Computer, laptop or charger with USB-A port
- Most current iPhone, iPad and iPod devices

Package Includes

M100-010-HD Heavy-Duty USB Sync/Charge Cable with Lightning Connector, 10-ft. (3.05 m)

TRIPP-LITE

NPUT Maximum Input Amps 2 POWER	Ochla Tara		
Maximum Input Ampa 2 POWER View Polivery (PD) Charging View Polivery (PD) Charging No CHARGING Total Charging Watts Total Charging Watts 12 PHYSICAL Biack: White Cable Jacket Color Biack: White Cable Jacket Color Biack: White Cable Jacket Material TPE Cable Jacket Material Wie Cable Jacket Material View 1 Cable Jacket Material View 1 Cable Jacket Material 26/19 Cable Jacket Material 10 Cable Length (th.) 10 Cable Length (th.) 120 × 2.80 x 5.20 Shipping Dimensions (twot / in.) 1.20 x 2.80 x 5.20 Shipping Meight (kg) 0.12 Lum Packaging Type Box ENVIRONMENTAL Degrating Tamperature Range Oparating Tamperature Range 4* to 10% F (20* to 80°C) Storage Temperature Range 9% to 80% RH, Non-Condensing Depresert Provided to Connected 12W (5V/2.4A) Connector J USB A (MALE)	Cable Type	Passive	
POWER No Shipport No CHARGING Total Charging Watts 12 PHYSICAL TPE, PVC, Nylon, Aramid Fiber PHYSICAL Cable Jacket Color Black; White Cable Jacket Color Cable Jacket Color Black; White Cable Jacket Rating Cable Jacket Rating VW-1 Cable Cable Outer Diameter (OD) Kire Gauge (AWC) 26/19 Cable Jacket Rating Cable Length (ft.) 10 Cable Length (ft.) Cable Length (ft.) 120 Stripping Meight (kg) Shipping Meight (kg) 0.12 ULL Uhr Packaging Type Box Environmentation Environmentations (troot / in.) 1.20 × 2.80 × 5.20 Stripping Weight (kg) Dyparating Temperature Range -4* to 140°F (-20° to 60°C) Storage Temperature Range Environmentation Cable Accentation 60°C) Storage Temperature Range <	INPUT		
Support No Support No CHARCING 12 Total Charging Watts 12 PHYSICAL Image: Construction PLP PVC, Nylon, Aramid Fiber Cable Jacket Color Black: White Image: Color Cable Jacket Color Black: White Cable Jacket Material TPE Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Carp Immeter (OD) 4.2mm Wire Gauge (AWG) 26/19 Cable Length (ft.) 10 Cable Length (ft.) 120 Cable Length (m) 3.05 Cable Length (m) 1.20 × 2.60 × 5.20 Shipping Dimensiona (hwd / in.) 1.20 × 2.60 × 5.20 Shipping Veight (kg) 0.12 Dow Dow ENVIRONMENTAL Concertaing Temperature Range Af' to 176°F (-20° to 60°C) Storage Temperature Range Af' to 076°F (-20° to 60°C) Storage Temperature Range Operating Humidity Range 0% to 60% RH, Non-Condensing Deriver(Solid to Connectod Derive(S	Maximum Input Amps	2	
Support No CHARGING I Total Charging Watts 12 PHYSICAL Image: Charging Watts Image: Charging Watts Cable Jacket Color Black: White Image: Charging Watts Cable Jacket Color Black: White Image: Charging Watts Cable Jacket Color Black: White Image: Charging Watts Cable Jacket Rating VW-1 Image: Charging Watts Cable Jacket Rating VW-1 Image: Charging Chargi	POWER		
Total Charging Watts 12 PHYSICAL Material of Construction TPE, PVC, Nylon, Aramid Fiber Cable Jacket Color Black; White Cable Jacket Color Cable Jacket Material TPE Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Douter Diameter (OD) 4.2mm Aumm Cable Jacket Rating VW-1 Cable Douter Diameter (OD) 4.2mm Stripping Cable Length (ft.) 10 Cable Jacket Rating VW-1 Cable Length (ft.) 10 Stripping Dimensions (hwd / in.) 1.20 Stripping Dimensions (hwd / in.) 1.20 x 2.60 x 5.20 Shipping Dimensions (hwd / in.) 1.20 x 2.60 x 5.20 Stripping Weight (kg) 0.12 Unit Packaging Type Box Storage Temperature Range 4* to 140*F (-20* to 60°C) Storage Temperature Range -4* to 176*F (-20* to 60°C) Storage Temperature Range 9% to 90% RH, Non-Condensing Storage Temperature Range 9% to 90% RH, Non-Condensing Storage Humidity Range 9% to 90% RH, Non-Condensing Connector S Storage Length to Connected 12W (sV/z.4A	USB Power Delivery (PD) Charging Support	No	
PHYSICAL Waterial of Construction TPE, PVC, Nylon, Aramid Fiber Cable Jacket Color Black; White Cable Jacket Material TPE Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 4.2mm Wire Gauge (AWG) 26/19 Cable Longth (ft.) 10 Cable Length (m) 3.05 Cable Length (m) 1.20 Shipping Dimensions (hvd / in.) 1.20 x 2.60 x 5.20 Shipping Weight (kg) 0.12 Unit Packaging Type Box Environmentature Range 4º to 140°F (-20° to 60°C) Storage Temperature Range 4º to 176°F (-20° to 60°C) Storage Temperature Range 4º to 176°F (-20° to 60°C) Operating Humidity Range 0% to 90% RH, Non-Condensing Owice Provided to Connected 12W (5V/2.4A) Device(s) 12W (5V/2.4A) Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel	CHARGING		
Material of Construction TPE, PVC, Nylon, Aramid Fiber Cable Jacket Color Black; White Cable Jacket Material TPE Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Jacket Rating 26/19 Cable Outer Diameter (OD) 4.2mm Wire Gauge (AWG) 26/19 Cable Length (ft.) 10 Cable Length (m) 3.05 Cable Length (m) 1.20 × 2.60 × 5.20 Shipping Dimensions (hwd / in.) 1.20 × 2.60 × 5.20 Shipping Type Box EnvironMENTAL Derating Temperature Range A* to 140°F (-20° to 60°C) Storage Temperature Range 4* to 176°F (-20° to 60°C) Storage Temperature Range Operating Temperature Range 4* to 176°F (-20° to 60°C) Consector Name 20% to 90% RH, Non-Condensing Power Provided to Connected 12W (6V/2.4A) Connector 1 USB A (MALE) Evertee(s) USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector	Total Charging Watts	12	
Cable Jacket Color Black; White Cable Jacket Material TPE Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Jacket Rating 26/19 Cable Longth (R) 26/19 Cable Length (R) 10 Cable Length (R) 3.05 Cable Length (N) 3.05 Cable Length (N) 120 Shipping Dimensions (Nwd / in.) 1.20 x 2.60 x 5.20 Shipping Weight (kg) 0.12 Unit Packaging Type Box EnVIRONMENTAL Deparating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -6% to 90% RH, Non-Condensing 9% to 90% RH, Non-Condensing Storage Lemidity Range 0% to 90% RH, Non-Condensing Power Provided to Connected Device (SV/2.4A) 12W (SV/2.4A) Connector 1 USB A (MALE) Storage Lemidity Range 0% to 90% RH, Non-Condensing Storage Lemidity Range 0% to 90% RH, Non-Condensing <tr< td=""><td colspan="3">PHYSICAL</td></tr<>	PHYSICAL		
Cable Jacket Material TPE Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 4.2mm Wire Gauge (AWG) 26/19 Cable Length (It.) 10 Cable Length (m) 3.05 Cable Length (m) 1.20 Shipping Dimensions (hwd / in.) 1.20 x 2.60 x 5.20 Shipping Weight (kg) 0.12 Unit Packaging Type Box ENVIRONMENTAL Departing Temperature Range -4* to 140*F (-20* to 60*C) Storage Temperature Range -4* to 176*F (-20* to 60*C) Storage Temperature Range Operating Temperature Range -4* to 176*F (-20* to 60*C) Storage Temperature Range -4* to 176*F (-20* to 60*C) Operating Humidity Range 0% to 90% RH, Non-Condensing Storage Temperature Range -4* to 176*F (-20* to 60*C) Deverier(sv) 12W (5V/2.4A) Connector 1 USB A (MALE) Storage Lumidity Range 0% to 90% RH, Non-Condensing Storage Lumidity Range USB A (MALE) Storage Lumidity Range USB A (MALE	Material of Construction	TPE, PVC, Nylon, Aramid Fiber	
Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Jacket Rating 4.2mm Cable Jacket Rating 26/19 Cable Langth (ft.) 10 Cable Langth (ft.) 10 Cable Length (m) 3.05 Cable Length (m.) 120 Shipping Dimensions (hwd / in.) 1.20 x 2.60 x 5.20 Shipping Weight (kg) 0.12 Unit Packaging Type Box ENVEROMENTAL Enveromentation of the state stat	Cable Jacket Color	Black; White	
Cable Outer Diameter (OD) 4.2mm Wire Gauge (AWG) 26/19 Cable Length (ft.) 10 Cable Length (m) 3.05 Cable Length (m) 1.20 × 2.60 × 5.20 Shipping Dimensions (hwd / in.) 1.20 × 2.60 × 5.20 Shipping Weight (kg) 0.12 Unit Packaging Type Box ENVIROMENTAL Doperating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 176°F (-20° to 60°C) Operating Temperature Range -4° to 176°F (-20° to 80°C) Operating Temperature Range -4° to 176°F (-20° to 80°C) Operating Humidity Range 0% to 90% RH, Non-Condensing Power Provided to Connected 12W (5V/2.4A) ENTECTIONS 12W (5V/2.4A) Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel	Cable Jacket Material	TPE	
Wire Gauge (AWG) 26/19 Cable Length (ft.) 10 Cable Length (m) 3.05 Cable Length (in.) 120 Shipping Dimensions (hwd / in.) 1.20 x 2.60 x 5.20 Shipping Weight (kg) 0.12 Unit Packaging Type Box Environmentation of the state of the st	Cable Jacket Rating	VW-1	
Cable Length (ft.) 10 Cable Length (m) 3.05 Cable Length (in.) 120 Shipping Dimensions (hwd / in.) 1.20 x 2.60 x 5.20 Shipping Weight (kg) 0.12 Unit Packaging Type Box Environmentation Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 176°F (-20° to 60°C) Operating Humidity Range 0% to 90% RH, Non-Condensing Operating Humidity Range 0% to 90% RH, Non-Condensing Power Provided to Connected 12W (5V/2.4A) Connector 1 USB A (MALE) Side A - Connector 1 LIGHTNING (MALE) Connector Plating Nickel	Cable Outer Diameter (OD)	4.2mm	
Cable Length (m) 3.05 Cable Length (in.) 120 Shipping Dimensions (hwd / in.) 1.20 x 2.60 x 5.20 Shipping Weight (kg) 0.12 Unit Packaging Type Box ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Temperature Range -4° to 176°F (-20° to 80°C) Operating Humidity Range 0% to 90% RH, Non-Condensing Operating Humidity Range 0% to 90% RH, Non-Condensing Power Provided to Connected Device(s) 12W (5V/2.4A) CONNECTIONS Side A - Connector 1 Side B - Connector 1 USB A (MALE) LiGHTNING (MALE) LiGHTNING (MALE) Connector Plating Nickel	Wire Gauge (AWG)	26/19	
Cable Length (in.) 120 Shipping Dimensions (hwd / in.) 1.20 x 2.60 x 5.20 Shipping Weight (kg) 0.12 Unit Packaging Type Box ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 176°F (-20° to 80°C) Operating Humidity Range 0% to 90% RH, Non-Condensing Storage Humidity Range 0% to 90% RH, Non-Condensing Power Provided to Connected 12W (5V/2.4A) Storage A: Connector 1 USB A (MALE) Side A - Connector 1 USB A (MALE) LIGHTNING (MALE) Connector Plating Nickel	Cable Length (ft.)	10	
Shipping Dimensions (hwd / in.) 1.20 x 2.60 x 5.20 Shipping Weight (kg) 0.12 Unit Packaging Type Box ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 176°F (-20° to 80°C) Operating Humidity Range 0% to 90% RH, Non-Condensing Storage Humidity Range 0% to 90% RH, Non-Condensing Power Provided to Connected 12W (5V/2.4A) CONNECTIONS 12W (5V/2.4A) Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Nickel Nickel	Cable Length (m)	3.05	
Shipping Weight (kg) 0.12 Unit Packaging Type Box ENVIRONMENTAL ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 176°F (-20° to 80°C) Operating Humidity Range 0% to 90% RH, Non-Condensing Storage Humidity Range 0% to 90% RH, Non-Condensing Power Provided to Connected 12W (5V/2.4A) EXENSE USB A (MALE) Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Non-Condenctor 1 LIGHTNING (MALE)	Cable Length (in.)	120	
Unit Packaging Type Box ENVIRONMENTAL -4° to 140°F (-20° to 60°C) Operating Temperature Range -4° to 176°F (-20° to 60°C) Storage Temperature Range -4° to 176°F (-20° to 80°C) Operating Humidity Range 0% to 90% RH, Non-Condensing Storage Humidity Range 0% to 90% RH, Non-Condensing Power Provided to Connected 12W (5V/2.4A) ECONNECTIONS USB A (MALE) Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Nickel Nickel	Shipping Dimensions (hwd / in.)	1.20 x 2.60 x 5.20	
ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 176°F (-20° to 80°C) Operating Humidity Range 0% to 90% RH, Non-Condensing Storage Humidity Range 0% to 90% RH, Non-Condensing Power Provided to Connected 12W (5V/2.4A) CONNECTIONS Side A - Connector 1 Side B - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel	Shipping Weight (kg)	0.12	
Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 176°F (-20° to 80°C) Operating Humidity Range 0% to 90% RH, Non-Condensing Storage Humidity Range 0% to 90% RH, Non-Condensing Power Provided to Connected 12W (5V/2.4A) CONNECTIONS 12W (5V/2.4A) Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel	Unit Packaging Type	Box	
Storage Temperature Range -4° to 176°F (-20° to 80°C) Operating Humidity Range 0% to 90% RH, Non-Condensing Storage Humidity Range 0% to 90% RH, Non-Condensing Power Provided to Connected 12W (5V/2.4A) CONNECTIONS 12W (5V/2.4A) Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel	ENVIRONMENTAL		
Operating Humidity Range 0% to 90% RH, Non-Condensing Storage Humidity Range 0% to 90% RH, Non-Condensing Power Provided to Connected 12W (5V/2.4A) CONNECTIONS 12W (5V/2.4A) Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel	Operating Temperature Range	-4° to 140°F (-20° to 60°C)	
Storage Humidity Range 0% to 90% RH, Non-Condensing Power Provided to Connected 12W (5V/2.4A) connectrions USB A (MALE) Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Nickel Nickel	Storage Temperature Range	-4° to 176°F (-20° to 80°C)	
Power Provided to Connected 12W (5V/2.4A) CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel	Operating Humidity Range	0% to 90% RH, Non-Condensing	
Power Provided to Connected 12W (5V/2.4A) CONNECTIONS Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel	Storage Humidity Range	0% to 90% RH, Non-Condensing	
Side A - Connector 1 USB A (MALE) Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel	Power Provided to Connected Device(s)	12W (5V/2.4A)	
Side B - Connector 1 LIGHTNING (MALE) Connector Plating Nickel	CONNECTIONS		
Connector Plating Nickel	Side A - Connector 1	USB A (MALE)	
	Side B - Connector 1	LIGHTNING (MALE)	
Contact Plating Gold	Connector Plating	Nickel	
	Contact Plating	Gold	



1000 Eaton Boulevard Cleveland, OH 44122 United States

Connector Style	Straight	
FEATURES & SPECIFICATIONS		
USB Specification	USB 2.0 (up to 480 Mbps)	
Data Transfer Rate	480 Mbps	
Angled Plug	No	
STANDARDS & COMPLIANCE		
Product Certifications	MFi	
Product Compliance	RoHS; REACH; UKCA	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	2-year limited warranty	



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.