


UNIT:mm



Technical requirements:

- 1 electrical testing requirements: 100% through 15 mobile phone test, data synchronization normal
- USB DC300V 20MΩ 0.1S no open circuit, short circuit, high pressure and other adverse
- 2 appearance: shell scratch, line no stains, forming without deformation, shrinkage, variegated, flash and other undesirable

④	TUBE	1	BLACK TUBE, OD6.0mm, L=18mm, 125°C 600V					
	COPPER FOIL	1	W=5*l=15mm, DOUBLE-SIDE COPPER FOIL					
	IN MOLD	3.7g	BLACK 45P TPE					
	OVER MOLD	1g	IP-5 MATERIAL: PC BLACK WHITE PROTECTIVE FILM					
③	SNAP-FIT	1g	IP-5 SNAP-FIT MATERIAL: PC BLACK					
	SHIELD CASE	1	C48 SHIELD CASE UP COVER, THICKNESS 0.3mm, WHITE"OP90" LOGO					
	IS CONNECTOR	1	C48 SHIELD CASE UP COVER, THICKNESS 0.3mm, WHITE"OP90" LOGO					
	IN MOLD	4.5g	C48 THE ORIGINAL CONNECTOR					
	OVER MOLD	1g	BLACK 45P TPE					
②	CONNECTOR	1g	IP-5 MATERIAL: PC BLACK, WHITE PROTECTIVE FILM					
	CALBE	1	USB A MALE SHORT BODY SOLID TYPE, WHITE A TIN COP PEARL NICKLE PLATED FINE BINDING LINE, WHITE INSULATION RATED TEMPERATURE 250-270, PIN G/F, BETWEEN 4P WHITE SHELL, IS SHORT, PHONE DEDICATED					
①	CALBE	1	3C+3D+1500D Huang Dansi+144 BRAID+AL 0D2.6mm, TPE BLACK JACKET					
	NO.							

CNC Tech, LLC
Industrial Cable and Connector Technology

DRAWN	Andy	DRAWING NO	
CHECKED		CUSTOMER	CNC
APPROVAL		ITEM NO.	104-1030-BL-00200
DECIDED		DATE	2014-11-06
VERSIONS/EDITION	A/0	PROJECTION	