



Product: [1387LP](#)

Lighting & Automation, 1 Pair 22 AWG, 2 Conductor 18 AWG, CMP

### Product Description

Lighting & Automation Cable, 1 (data) pair 22 AWG stranded (7x30) bare copper, FEP insulation, Beldfoil® shield with drain, and 2 conductor 18 AWG stranded (19x30) bare copper unshielded, FEP insulation (power), CMP rated PVDF jacket

### Technical Specifications

#### Product Overview

Suitable Applications:	Multi-Media & Lighting Automation / Control, Lutron® Sivoia® QS System, Motor Drive Unit
------------------------	--

#### Construction Details

##### Conductor

Element	No. of Elements	Size	Stranding	Material
Pair(s)	1	22 AWG	7x30	BC - Bare Copper
Conductor(s)	2	18 AWG	19x30	BC - Bare Copper

##### Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Pair(s)	FEP - Fluorinated Ethylene Propylene	0.015 in (0.38 mm)	0.066 in (1.7 mm)	Purple & White
Conductor(s)	FEP - Fluorinated Ethylene Propylene	0.011 in (0.28 mm)	0.058 in (1.5 mm)	Red & Black

##### Inner Shield

Shield Type	Material	Coverage	Drainwire Type
Tape	Bi-Laminate (Alum+Poly)	100%	24 AWG (7x32) TC

##### Outer Shield

<b>Material</b>
No Shield

##### Outer Jacket

Material	Nom. Thickness	Nom. Diameter
PVDF - Polyvinylidene Fluoride	0.017 in (0.43 mm)	0.228 in (5.79 mm)

Overall Cable Diameter (Nominal):	0.228 in (5.79 mm)
-----------------------------------	--------------------

#### Electrical Characteristics

##### Electricals

Element	Nom. Conductor DCR	Nom. Inner Shield DCR	Nom. Capacitance Cond-to-Cond	Max. Current
Pair(s)	17.2 Ohm/1000ft	17.42 Ohm/1000ft (57.15 Ohm/km)	21.2 pF/ft (69.6 pF/m)	34 Amps per conductor @ 30°C
Conductor(s)	6.9 Ohm/1000ft (23 Ohm/km)			17 Amps per conductor @ 30°C

##### Voltage

<b>UL Voltage Rating</b>
300 V

#### Mechanical Characteristics

## Temperature

UL Temperature	Operating
150°C	-40°C to +150°C

## Bend Radius

Stationary Min.	Installation Min.
2.3 in (58 mm)	2.3 in (58 mm)

Max. Pull Tension:	73.1 lbs (33.2 kg)
Bulk Cable Weight:	39 lbs/1000ft

## Standards and Compliance

Environmental Suitability:	Indoor - Plenum, Indoor
Flammability / Reaction to Fire:	NFPA 262 (UL 910), FT6
NEC / UL Compliance:	Article 800
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark
Non-Plenum Number:	1385LA

## Product Notes

Notes:	Sequential footage marking every two feet.
--------	--

## History

Update and Revision:	Revision Number: 0.393 Revision Date: 05-03-2023
----------------------	--

## Part Numbers

### Variants

Item #	Color	Putup Type	Length	UPC
1387LP 009500	White	Reel	500 ft	612825114086

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.