


NOTES: UNLESS OTHERWISE SPECIFIED

1. P/N: PICOCOLOR
HOUSING & PLUNGER: MOLDED NYLON. AVAILABLE IN TEN COLORS.
CONTACT BLADE: GOLD PLATED BeCu.
SPRING: STAINLESS STEEL.
2. P/N: 9205-HS
INSULATOR: HEAT SHRINK TUBING. BLACK.
BODY: NICKEL UNDERPLATED BRASS.
CONTACT: GOLD FLASH OVER NICKEL UNDERPLATED BRASS.
GOLD FLASH BeCu SPRING.
3. P/N: W-701/COLOR
28AWG TINNED COPPER
0.047 [1.19] O.D. PVC INSULATION
AVAILABLE IN TEN COLORS.
4. PERFORMANCE
MAXIMUM CURRENT: 1.0 AMPS
MAXIMUM VOLTAGE: HANDHELD: 33VAC/60VDC
HANDS FREE: 600 W.V.D.C.
MAXIMUM TEMPERATURE: 176°F (80°C)

LTR	REVISIONS		DATE	APPROVED
	DESCRIPTION			



		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS DECIMALS ANGLES ± .XX ± ± .XXX ±	CONTRACT NO.		E-Z-HOOK DIVISION OF TEKTEST INC. ARCADIA, CA 91006 U.S.A.
			APPROVALS	DATE	
		MATERIAL SEE NOTE.	DRAWN R.L.	5/13	DESCRIPTION PICO HOOK TO 0.025 [0.64] SQ. SOCKET (28AWG)
		FINISH SEE NOTE.	APPROVED BY		
NEXT ASSY	USED ON				SIZE CODE IDENT NO. DRAWING NO. REV. B 08505 P703
APPLICATION		DO NOT SCALE DRAWING			SCALE 1:1 SHEET 1 OF 1