





#### Description

 IQXT-205-3-18 is a 2.0 x 1.6mm SMD Temperature Compensated Crystal Oscillator (TCXO) in a hermetically sealed package with a wide operating temperature range.

■ Model IQXT-205-3-18

Model Issue number

#### **Frequency Parameters**

Frequency
Frequency Tolerance Max
Tolerance Condition
Frequency Stability
19.20MHz
±1.50ppm
25°C ±2°C
±0.50ppm

■ Operating Temperature Range -40.00 to 105.00°C

■ Ageing ±1ppm max per year @ 25°C

±2°C

 Frequency Tolerance: Referred to nominal frequency before reflow soldering.

 IR Reflow Resistance (@ 25°C ±2°C ref to frequency before reflow): ±1ppm max, 24hrs after reflow

■ Supply Voltage Variation (@ ±5% change): ±0.1ppm max

■ Load Variation (@ ±10% change): ±0.1ppm max

#### **Electrical Parameters**

Supply VoltageCurrent Draw Max1.8V ±5%1.500mA max

Absolute Maximum Ratings: Supply Voltage: -0.6V to 4.6V

# **Output Details**

Output Compatibility Clipped Sine
□ Drive Capability 10kΩ//10pF

Output: DC coupled

Output Level: 0.8V pk-pk min

Start Up Time (90% of V pk-pk): 2ms max

Start Up Time (within ±0.5ppm): 2ms max

# **Noise Parameters**

■ Phase Noise (typ): -135dBc/Hz @ 1kHz

#### **Environmental Parameters**

Storage Temperature Range: -40 to 105°C

### **Manufacturing Details**

RoHS Terminations
NiAu

■ RoHS Reflow Temp +250°C ±10°C for 10 sec max

# Compliance

RoHS Status (2015/863/EU)
REACh Status
MSL Rating (JDEC-STD-033):
2


#### **Packaging Details**

■ Pack Style: Reel Tape & reel in accordance with EIA-481-D

Pack Size: 3,000

Alternative packing option available

# Outline (mm)



#### Sales Office Contact Details:

UK: +44 (0)1460 270200 USA: +1.760.318.2824 Email: info@iqdfrequencyproducts.com Web: www.iqdfrequencyproducts.com