

## Antenna cable - RAD-PIG-EF316-N-RSMA - 2701402

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Adapter cable as control cabinet feed-through, N (female) -> RSMA (male), impedance: 50 Ω, length: 0.5 m



### Product Features

- As an adapter between devices and cables

### Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	60.0 g
Custom tariff number	85442000
Country of origin	Poland

### Technical data

#### Dimensions

Fixed cable length	50 cm
External diameter	2.50 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

#### General

Connection 1	Connector connection
Connection method	RSMA (male)
Connection 2	Connector connection
Connection method	N (female)
Cable type	EF 316
Outer sheath, material	RADOX®(LSFH)
Minimum bending radius	12.50 mm
Frequency range	900 MHz
	2.4 GHz

# Antenna cable - RAD-PIG-EF316-N-RSMA - 2701402

## Technical data

### General

	5 GHz
Impedance	50 Ω

### Attenuation

868 / 900 MHz	0.6 dB
2.4 GHz	1 dB
5 GHz	1.4 dB

## Classifications

### eCl@ss

eCl@ss 4.0	27060805
eCl@ss 4.1	27060805
eCl@ss 5.0	27061805
eCl@ss 5.1	27061805
eCl@ss 6.0	27061805
eCl@ss 7.0	27061805
eCl@ss 8.0	27061802

### ETIM

ETIM 4.0	EC000019
ETIM 5.0	EC000019

### UNSPSC

UNSPSC 6.01	26121608
UNSPSC 7.0901	26121608
UNSPSC 11	26121608
UNSPSC 12.01	26121608
UNSPSC 13.2	26121608

## Approvals

### Approvals

---

Approvals

EAC / EAC

---

## Antenna cable - RAD-PIG-EF316-N-RSMA - 2701402

### Approvals

Ex Approvals

---

Approvals submitted

---

### Approval details

EAC
-----

EAC
-----

---