


THIS IS ISSUED IN STRICT CONFIDENCE THAT IT IS NOT USED AS A BASIS FOR MANUFACTURE OR SALE AND THAT IT IS NOT COPIED, REPRINTED OR DISCLOSED TO A THIRD PARTY EITHER WHOLLY OR IN PART WITHOUT THE PRIOR WRITTEN CONSENT OF CAL TEST ELECTRONICS, INC.

NOTES:

- SPECIFICATION:
 JACKET: SILICONE. OD: .083±.008 (2.1 mm)
 CONDUCTOR: BARE COPPER, STRANDING 104 x 0.07 mm = 0.40 mm², 21 AWG.
- RATING:
 VOLTAGE: 1,000 V CAT III PER IEC 61010-031
 CURRENT: 6 A MAX.
 TEMPERATURE: -60° C TO +180° C.
- AVAILABLE IN 3 STANDARD LENGTHS AND 6 COLORS - SEE MODEL NUMBER BELOW.

REVISIONS			
REV.	DESCRIPTIONS	DATE	APPROVED
-	CLASS A RELEASED	7/11/99	
A	UPDATED FORMAT w/ CAGE CODE	4/18/04	



MODEL NUMBER

CT2883-#-XXX

COLOR: 0 - BLACK
 2 - RED
 4 - YELLOW
 5 - GREEN
 6 - BLUE
 9 - WHITE

LENGTH: 10 - 10 m PACKAGE
 50 - 50 m SPOOL
 100 - 100 m SPOOL

THIRD ANGLE PROJECTION		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS DECIMALS ± 1/32 .XX ± .02 .XXX ± .005 DO NOT SCALE DRAWING	CONTRACT NO.		Cal Test Electronics 22820 Savi Ranch Parkway Yorba Linda, CA 92887-4610	
			APPROVALS	DATE	TITLE	
MATERIAL		DRAWN	WDH	7/11/99		WIRE, TEST LEAD, SILICONE JACKET, 0.40 mm ² , 21 AWG, 6 A
FINISH		CHECKED			SIZE	REV.
NEXT ASSY	USED ON	ENGR.			A	A
APPLICATION		DESIGN ACTIVITY			CAGE CODE	DWG. NO.
					A	43F45
					P288300	
					SCALE	SHEET
					NONE	1 OF 1