THIS	COPY IS PRO	OVIDED OI	N A RESTR	ICTED BA	S AND IS NOT TO BE USED IN ANY WAY D	ETRIMENT	AL TO THE INTERESTS		ORP.		
			- 56" (1	42 mm)	>		PANDUIT PART N	0. WI	EIGHT:		
			9.0 (1	42 1111)		GPST Tool		lb./each 35 g./each)			
							GPSTB Blade		8 lb./each 2 g./each)		
			GPST	(FRONT		NOTES:					
GI	PSTB (BLAD	((SIDE V 11" (54	.43" (11 mm)		 SEE CURRENT CATALOG FOR ADDITIONAL PART NUMBER SUFFIXES TO INDICATE COLOR AND OR PACKAGE QUANTITY. SEE CATALOG FOR COMPLETE LIST OF PARTS APPLICABLE FOR USE WITH THIS PART. PARTS INCLUDED ARE: GPST SINGLE PUNCHDOWN TOOL GPSTB SINGLE REPLACEMENT BLADE DIMENSIONS IN PARENTHESES ARE IN METRIC. TERMINATES CABLE ON ALL GIGA-PUNCH[™] TYPE PRODUCTS. REVERSIBLE BIT PROVIDES OPTION OF TERMINATING WITHOUT CUTTING WIRE. 				
							GPST / GPST	ГВ СИЅТС		WING	
								CUSTOMER DRA	WING		
							ITEM REVISION NAME:				
							CG24580A	01_01	H AN		
							DIMENSIONAL TOLER	UNLESS OTHERWISE SPECIFIED, MATERIAL: DIMENSIONAL TOLERANCES ARE: HANDLE:			
							(.x) ± (.xxx) ± PLASTIC/STEEL (.xx) ± ANGLES ± BLADE: STEEL				
01	4-15-14	BLR	BJPU	ABJ	REDRAWN: NEW TEMPLATE			THIRD ANGLE DRAWING NUMBER: PROJECTION CG24580A01		ER:	
		1	1				DRAWN BY: DATE:	CHK SCALE			