### **ELCON**

TE Internal #: 194018-1


Rectangular Power Connectors, Header, Plug, Wire-to-Board, 5 Position, 600 mm [36 in] Centerline, Printed Circuit Board, UL 94V-0

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors











Rectangular Power Connector Type: Header

Connector & Housing Type: Plug
Connector System: Wire-to-Board

Number of Positions: 5

Centerline (Pitch): 600 mm [36 in]

## **Features**

#### **Product Type Features**

Product Type Features	
Header Type	Fully Shrouded
Rectangular Power Connector Type	Header
Connector & Housing Type	Plug
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	5
PCB Mount Orientation	Vertical
Contact Features	
PCB Contact Termination Area Plating Material Thickness	5.08 μm[200 μin]

Inline

Silver

36 A

Contact Layout

Contact Mating Area Plating Material

Contact Current Rating (Max)



Contact Type	Pin
PCB Contact Termination Area Plating Material	Silver
Contact Mating Area Plating Material Thickness	5.08 – 10.16 μm[200 – 400 μin]
Termination Features	
Termination Post & Tail Length	3.69 mm[.145 in]
Termination Method to Wire & Cable	Solder
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
PCB Mount Alignment Type	Standard Polarized Tail
Strain Relief	Without
Mating Alignment Type	Polarization
Mating Retention	With
Mating Alignment	With
PCB Mount Alignment	With
PCB Mount Retention	Without
Mating Retention Type	Locking Tab
Connector Mounting Type	Board Mount
Housing Features	
Centerline (Pitch)	600 mm[36 in]
Housing Color	White
Housing Material	Nylon GF
Dimensions	
Connector Height	14.73 mm
PCB Thickness (Recommended)	1.57 mm[.062 in]
Product Width	7.62 mm
Product Length	33.02 mm
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Power
Industry Standards	
CSA Rating	Certified, LR 16455



UL Rating	Recognized
Agency/Standard	CSA, UL, VDE
Approved Standards	UL E28476
UL Flammability Rating	UL 94V-0
Glow Wire Rating	Standard Part - Not Glow Wire
Packaging Features	
Packaging Quantity	25
Packaging Method	Bag

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





## Customers Also Bought

















## **Documents**

**Product Drawings** 

PIN ASSY..070

English

### **CAD Files**

Customer View Model

ENG\_CVM\_CVM\_194018-1\_C.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_194018-1\_C.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_194018-1\_C.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use



## Datasheets & Catalog Pages

SOFT\_SHELL\_PIN\_SOCKET\_CONNECTORS\_STANDARD\_DENSITY

English

**Product Specifications** 

**Application Specification** 

English

Agency Approvals

**VDE Certificate** 

English