



NOTE:

1. ELECTRICAL CHARACTERISTICS

- 1-1 RATING CURRENT: 3A AC/DC
 - 1-2 RATING VOLTAGE: 250V AC/DC
 - 1-3 WITHSTANDING VOLTAGE: 800V AC/1MINUTE
 - 1-4 OPERATING TEMPERATURE: -40°C~+105°C
 - 1-5 INSULATION RESISTANCE: 1000M ohm MIN
2. MATERIAL: REFER TO ORDERING CODE
3. FINISH: BRIGHT TIN PLATING
4. INSULATION O.D.: ø1.70MM MAX
- WIRE SIZE: AWG#22~26 (0.35~0.13mm²)
5. USED WITH AFCI 10156616
6. PRODUCT SPEC: GS-12-1595
7. ORDERING CODE: 10156617-X 0 0 X LF

MATERIAL 4-BRASS
2: PHOSPHOR BRONZE

PACKAGE 1: REEL

mat'l. code	ecn no	dr	date	surface	tolerance	projection	product family
A	New release	Jason	2020-2-19	ISO 1302	ISO 406 ISO	110°	MINITEK
B	ELX-N-36510	Jason	2020-4-2	tolerances unless otherwise specified	.X±.3 .XX±.20 .XXX±.10	mm	2.5PITCH BOARD-IN, R/A, TERMINAL
sheet index	revision	chr	engr	dr	engr	chr	dwg no
1	B	-	Jason Wang	Jason Wang	-	-	10156617
			Tim Yao	Tim Yao			sheet 1 of 1
							size A3