

72V External Battery Pack for Select Tripp Lite UPS Systems, 2U Rack/Tower, TAA

MODEL NUMBER: **BP72V18-2USTAA**



TAA-compliant external battery pack provides extended runtime for compatible 72V Tripp Lite UPS systems.

Features

Gives Your Compatible Tripp Lite UPS System Extended RuntimeThe BP72V18-2USTAA is compatible only with Tripp Lite's SU3000RTXLCDTAA and other UPS systems that specify the use of this battery pack. Not only does it provide extended runtime, but it can also be daisy-chained using its rear connector to additional external battery packs for even longer extended-run operation. Heavy-gauge cabling with high-current DC connectors is included for simple installation.

Mounts in 2U of Space in 19 in. 4-Post RacksThis battery pack's multi-use form factor supports mounting in 2U of space in EIA-standard 19-inch racks using the included 4-post rack-mounting brackets. The BP72V18-2USTAA is also compatible with Tripp Lite's 2-9USTAND for upright tower configuration, 2POSTRMKITWM for 2-post racks or wall installation and UPDHDEARKIT for 2-point front-rail rack installation without rear supports (all accessories sold separately).

TAA-Compliant for GSA Schedule PurchasesThe BP72V18-2USTAA is compliant with the Federal Trade Agreements Act for GSA Schedule purchases.

2-Year Warranty and Environmentally Responsible DesignThe BP72V18-2USTAA comes with a 2-year warranty. It's manufactured in compliance with strict RoHS specifications, reflecting Tripp Lite's commitment to environmental responsibility.

Specifications

OVERVIEW	
UPC Code	037332223678
INPUT	
Input Phase	Single-Phase

Highlights

- Connects to expandable 72V DC Tripp Lite UPS systems for extended runtime
- Daisy-chain connector supports additional battery packs for even longer runtime
- Mounts in 2U of space in 19 in. rack using included 4-post installation hardware
- Supports 2-post rack, wall or tower installation with optional accessories
- Complies with Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Applications

- Extends the runtime of your compatible Tripp Lite UPS system
- Daisy-chains to additional battery packs to provide even longer extended-run operation

Package Includes

- BP72V18-2USTAA 72V External Battery Pack, 2U Rack/Tower, TAA
- Rack-mounting hardware
- Owner's manual

BATTERY	
DC System Voltage (VDC)	72
UPS Connection	Attached cable with black 3-point DC connector
Typical Battery Lifespan	4-6 years typical (North America)
PHYSICAL	
Material of Construction	Steel
Rack Height	2U
External Battery Pack Form Factor	Rack/Tower
Installation Form Factors Supported with Included Accessories	4 post 19 inch rackmount
Installation Form Factors Supported with Optional Accessories	2 post rackmount (2-Post-Rack-Mount-Wall-Mount-Adapter-Kit-select-Rack-Mount-UPS-Systems~2POSTRMKITWM); Wallmount (2-Post-Rack-Mount-Wall-Mount-Adapter-Kit-select-Rack-Mount-UPS-Systems~2POSTRMKITWM); Tower (2U-9U-Tower-Stand-Kit-select-Rack-Mount-UPS-Systems~2-9USTAND); 2-4 post front rail rackmount (Heavy-Duty-2-post-Front-Mounting-Ear-Kit~UPSHDEARKIT)
Minimum Required Rack Depth (cm)	68.07
Minimum Required Rack Depth (inches)	26.8
Shipping Dimensions (hwd / in.)	9.00 x 28.00 x 26.00
Shipping Dimensions (hwd / cm)	22.86 x 71.12 x 66.04
Shipping Weight (lbs.)	129.00
Shipping Weight (kg)	58.51
Unit Dimensions (hwd / in.)	3.430 x 17.320 x 20.810
Unit Dimensions (hwd / cm)	8.6 x 44 x 52.8
Unit Weight (lbs.)	88.20
Unit Weight (kg)	40.01
WARRANTY & SUPPORT	
Product Warranty Period (U.S. & Canada)	2-year limited warranty
Product Warranty Period (International)	1-year limited warranty
Product Warranty Period (Mexico)	1-year limited warranty
Product Warranty Period (Puerto Rico)	1-year limited warranty
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available



1000 Eaton Boulevard
Cleveland, OH 44122
United States



© 2023 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.