

6		5		4	3		2	1	
S	EE DI	ETAIL	- "Z	"					J
)			1.0 FE	ET +0 -2 TAIL			1
			۸				-FLAG LABEL		БR н
			USE WI DISCON SERVIC CAUTIC AND FI WATTA	JTION-RISK OF SHOCK A TH LAMP BASE IN UP POSITION INECT PLUG BEFORE RELA CING. DN - TO REDUCE THE RISK OF E IRE, DO NOT EXCEED MARKE IGE OR STRING MAXIMUM WAT DDITIONAL STRING LOADS.	ONLY. MPING OR LECTRIC SHOCK D LAMPHOLDER TAGE INCLUDING	sembled in Me	EMPORARY LIGHTI CAT NO. <u>1301110049</u> DATE C 125 VOLT, 15 AMP MAX. MAX PER SOCKET: 200W T OR 35W CFL/L INDOOR USE ONI Woodhe	CODE <u>X XXXXXX</u> 1875W MAX. IYPE A INCAN. ED	G
THIS STRINGLIGHT IS INTENDED FOR INDOOR USE ONLY. DO NOT EXCEED MARKED SOCKET WATTAG STRING MAX. CURRENT. DO NOT CONNECT OR DISCONNECT WHEN WET. ONLY USE SELF-BALLASTED LAMPS IF A SELF-BALLASTED LAMP TYPE IS IDENTIFIED APPROPRIATE LAMP TYPES. DO NOT USE GE SURVIVOR OR ROUGH SERVICE TYPE LAMPS. FOR USE ONLY ON GFCI PROTECTED CIRCU ACCORDANCE WITH ARTICLE 590 OF THE N								MPS IF A DENTIFIED ON	F
			OF COI	ELECTRIC SHOC					
	IJĽ∕ ſ	ITEM	ח	ESCRIPTION		MATER		COLOR	
		11 EIVI 10		VERMOLD SOCKE	т				-
/	/	20		AP	1	NYLON		BLACK	D
	-	30	C	AF ABLE #12-3 SJTOV ATED AT 300V 60°0		PVC/C		YELLOW	/
		40	н	OT CONTACT CEN	TER	BRASS		PLAIN	
60		50	N	NEUTRAL CONTACT		BRASS		PLAIN	
		60	GROUNDING RING			BRASS		PLAIN	
		70	SCREWSHELL			NYLON		BLACK	$\neg \mid$
IERAL TOLE NLESS SPE)			SCALE NTS TITLE	DES		YELLOW THIRD ANGI PROJECTIO	 _E
ES \pm \pm ES \pm $\pm .005$ ES \pm $\pm .010$ DE \pm $\pm .020$ ANGULAR $\pm 1/2^{\circ}$							STRINGLIGHT (47.5 FT) 2-3 SJTOW YELLOW CABLE EMA 5-15P & NEMA L5-15R MOLEX INCORPORATED		
DRAFT WH APPLICAE MUST REN THIN DIMEI	IERE BLE MAIN	M	MATERIAL NO. DOCUMENT 1301110049 SIZE THIS DRAWING CONTAINS INF			SD-2	NO. SHEET NO. SHEET NO. 1 OF 1		
6	6 5		4		3		2	1	