




ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	NOTES
1	50-00396	Connector, stereo plug, 3.5xL20.5 mm, brass, nickel plated, molding style	1	
2	30-00177	Wire, 2C BC, 28 AWG, 300V, 80C, 3.8 mm, foil + shield, PVC	1	
3	24-00085	Overmold, PVC	1	black
4	Heat shrink	Heat shrink tube, black	1	covers end of jacket
5	Heat shrink	Heat shrink tube, black	1	covers shield



Notes:
Functionally equivalent components may be substituted



Wiring Diagram	
50-00396	wire color
A	red
B	white
C	shield

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>
A	3/22/2016	Initial release	DN <small>Digitally signed by DN Date: 2017.05.22 09:36:05 -07'00'</small>	RoHS compliant	
A1	7/15/2016	Modified collar exposure	Verified: GL <small>Digitally signed by GL Date: 2017.05.23 08:36:03 -07'00'</small>	Function test: no open, no short circuit, no intermittent	
A2	5/22/2017	Modified plug overmold	Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 915 mm, 3.5 mm 3C 90° 50-00396 audio plug to 5 mm tinned, 28 AWG, 30-00177 wire	
				Size: A Part number: 10-02143 Scale: 1:1	 Sheet 1 of 1