

SAFETY ORGANIZATION(S):

THIS FILTER HAS BEEN FORMALLY RECOGNIZED, CERTIFIED OR APPROVED BY THE LISTED AGENCY. THEREFORE, ALL TEST/REQUIREMENTS SPECIFIED IN THE LATEST REVISION OF THE FOLLOWING AGENCY STANDARDS HAVE BEEN MET.

- UL RECOGNIZED
- CSA CERTIFIED
- VDE APPROVED
- SEMKO APPROVED

OPERATING SPECIFICATIONS:

- LINE VOLTAGE/CURRENT, 6 AMP., 120/250 VAC
- LINE FREQUENCY, 50-60Hz

MAX. LEAKAGE CURRENT, EACH LINE TO GROUND

OPERATING AMBIENT TEMP. RANGE,

IN AN AMBIENT, I_0 , HIGHER THAN 40°C, THE MAXIMUM OPERATING CURRENT, I_0 , IS AS FOLLOWS,

$$I_0 = I_r \sqrt{\frac{95 - I_0}{45}}$$

RELIABILITY SPECIFICATIONS:

- STORAGE TEMPERATURE, -40°C TO +85°C
- HUMIDITY, 21 DAYS @ 40°C 95% RH
- CURRENT OVERLOAD TEST, 6 TIMES RATED CURRENT FOR 8 SECONDS

TEST SPECIFICATIONS:

- INDUCTANCE, .465 mH NOMINAL
- CAPACITANCE, (MEASURED @ 1 KHZ, 0.25 VAC MAX., 25°C ±1°C)
- LINE TO GROUND, .003µF ±20%
- LINE TO LINE, .047µF ±20%
- DISCHARGE RESISTOR, 1.5 MΩ
- LINE/GROUND AND LINE/LINE, 6000 MΩ (MIN) AT 100 VDC
- INSULATION RESISTANCE (W/O DISCHARGE RESISTOR), 20°C AND 50% RH

RECOMMENDED RECEIVING INSPECTION HIPOTL:

- LINE TO GROUND, 2250 VDC FOR 1 MINUTE
- LINE TO LINE, 1450 VDC FOR 1 MINUTE

FILTER APPROVAL:
 THE BEST WAY TO SELECT AND QUALIFY A FILTER IS FOR YOUR ENGINEERING TO TEST THE UNIT IN YOUR EQUIPMENT.

TOLERANCE EXCEPT AS NOTED



DECIMAL, .XXX .XX .X ANGLES ± 1°
 ENGLISH, ±.020 METRIC, ±

MATERIAL:

AS SUPPLIED

FINISH:

AS SUPPLIED



THIS FILTER LINE AND LOAD ARE REVERSED; THE SOCKET IS LOAD.



FREQUENCY MHz	.01	.05	.1	.15	.5	1	3	5	10	30
COMMON	1	4	10	22	28	37	42	46	47	
DIFF.	1	2	10	14	20	33	42	40		

This document is proprietary to CORCOM INC. and is not to be reproduced nor used for manufacturing purposes except on CORCOM's order or prior written consent.



ACCESSORY OUTLET FILTER

SCALE	DATE	DRG. NO.	REV.
NTS	11-5-90		6EBF1.02
DRW. BY	ORIGINATOR		
CFW	CFW		

*RESISTOR ADDED TO PRODUCT BUILT AFTER 3-30-92 (9212)