



Product: [8434](#)

Electronic, 1 Pr+2 C #25 Str TC+TCCS, PE Ins, IS/OS, PVC Jkt



REPRESENTATIVE IMAGE

Request Sample

Product Description

Electronic, 1 Pair+2 Conductors 25AWG (7x33) Tinned Copper+Tinned Copper Covered Steel, PE Insulation, Individual & Overall Beldfoil® Shield, PVC Outer Jacket

Technical Specifications

Product Overview

Suitable Applications:	low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; computer communication; panel wiring
------------------------	---

Construction Details

Conductor

Element	No. of Elements	Size	Stranding	Material
Pair(s)	1	25	7x33	TC+TCCS - Tinned Copper + Tinned Copper Covered Steel
Conductor(s)	2	25	7x33	TC+TCCS - Tinned Copper + Tinned Copper Covered Steel

Insulation

Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
PE - Polyethylene	0.013 in (0.33 mm)	0.047 in (1.2 mm)	Red & Black
PE - Polyethylene	0.013 in (0.33 mm)	0.047 in (1.2 mm)	Green, White

Inner Shield

Element	Shield Type	Material	Coverage	Drainwire Type	Notes
Pair(s)	Tape	Bi-Laminate (Alum+Poly)	100%	25 AWG (7x33) TC+TCCS	Drain Wire -25 AWG 3X33 SEPTC+4X33 STCCS
Conductor(s)	No Shield				

Table Notes:	Shorting Fold (Foil-out)
--------------	--------------------------

Outer Shield

Shield Type	Material	Coverage
Tape	Bi-Laminate (Alum+Poly)	100%

Outer Jacket

Material	Nom. Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.02 in (0.51 mm)	0.165 in

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Pair(s)	45.5 Ohm/1000ft	25 pF/ft (82 pF/m)	40 pF/ft (130 pF/m)	1.7 Amps per Conductor at 25°C
Conductor(s)	35.7 Ohm/1000ft (117 Ohm/km)			

Voltage

Voltage Rating
400 V

Mechanical Characteristics

Temperature

UL Temperature	Operating
80°C	-20°C To +80°C

Bend Radius

Stationary Min.	Installation Min.
1.65 in (41.9 mm)	1.65 in

Max. Pull Tension:	26.4 lbs (12.0 kg)
Bulk Cable Weight:	12 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor
Flammability / Reaction to Fire:	IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark

History

Update and Revision:	Revision Number: 0.420 Revision Date: 05-05-2023
----------------------	--

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC	Footnote
8434 060100	Chrome	Reel	100 ft	612825207047	
8434 060500	Chrome	Reel	500 ft	612825207061	
8434 0601000	Chrome	Reel	1,000 ft	612825207054	C
8434 060U1000	Chrome	UnReel	1,000 ft	612825207030	

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.