



NOTE

1. MATERIAL : NYLON 66 UL94V-2
2. APPLICABLE TERMINAL : 35028-9010
3. MATED WITH HEADER : 35205-***I*, 35208-****

LEGEND

35109 - ** I *

COLOR : ϕ --- NATURAL
I --- BLACK

CKT(16,20)

45.0	49.9	52.6	35109-20I*	35109-20I*	20
35.0	39.9	42.6	35109-16I*	35109-16I*	16
C	B	A	EDP. NO.	ENG. NO.	CKT.

DO NOT SCALE DRAWING
DIMENSION IN METRIC

		ASS'Y PART		QTY/REEL OR PACK	SURFACE AREA	MATERIAL	WIRE RANGE	GENERAL TOLERANCES	MOLEX-KOREA CO.,LTD.	
		DESCRIPTION	ENG.NO.		MM ²	NYLON 66 UL94V-2	AWG: ---	DIM. : 0.30		
C	REVISED	95-044	95-4/10				MM ² : ---	ANGLE : 1°	REVISE ONLY ON CAD SYSTEM	
B	RELEASED	92-017	92-3/27	DIE NO.	LAYOUT NO.	<input checked="" type="checkbox"/> : CRITICAL <input checked="" type="checkbox"/> : MAJOR <input type="checkbox"/> : MINOR () : REFERENCE	INSULATION RANGE	TITLE: METER CONN.FEMALE HOUSING		
A	NEW RELEASED	91-020	91-10/25	WIRE CRIMP WIDTH	INS. CRIMP WIDTH	DRAWN BY H.S.SHIN	---	ENG.NO.	SD 35109-***I*	
I	RELEASED	91-020	91-5/20	APPL FEED	IBDW	CHK'D BY	---	REV	C	
0	TEMPORATY RELEASED	91-020	91-2/12	DIE FEED	WBDW	APP'D BY	---	SCALE	CAD 2 - 1	
LTR	REVISION RECORD	ECN	DR. CHK	DATE						