



N-07-50-MH-9-C-XX

ⓓ

N = CABLE TIES

CABLE TIE LENGTH
INCHES
(ROUNDED)

TENSILE STRENGTH
18 = 18 LBS
40 = 40 LBS
50 = 50 LBS
120 = 120 LBS

TIE TYPE
(BLANK) = STANDARD TIE
ID = IDENTIFICATION
MH = MOUNTING HOLE

INTERNAL DESIGNATOR

AMOUNT PER PACKAGE
C = 100
D = 500
M = 1000

COLORS
0 = UV BLACK
9 = NATURAL
30 = HEAT STABILIZED

SALES DRAWING

REMOVE BASE INFO EC NO: ETC2007-0295 DRWN: TBOANN02007/02/13 CHKD: JMACNEIL 2007/02/13 APPR: JMACNEIL 2007/02/14	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY	
	DESCRIPTION ▽ = 0 ∇ = 0		mm	INCH	DIMENSION STYLE IN/MM		TITLE	
		4 PLACES	±---	±---	DRAWN BY B.ENDERL	DATE 04/05/11	19252 SERIES ENGINEERING NUMBERS CABLE TIES MOLEX INCORPORATED	
		3 PLACES	±---	±---	CHECKED BY H.BEITZL	DATE 04/05/11		
2 PLACES	±---	±---	APPROVED BY R.DERROSS	DATE 04/05/11	MATERIAL NO.	DOCUMENT NO.	SHEET NO.	
1 PLACE	±---	±---	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		04/05/11	SEE CHART	SD-19252-001	1 OF 1
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION								