
	THE REVISION STATUS OF ALL SHEETS OF THIS DRAWING IS THE SAME AS SHEET 1						
REV	DESCRIPTION	DATE	BY				
Α	INITIAL RELEASE	10/27/22	YA				
-							



Dwg. Number	Customer P/N	Times P/N	Length(L) in 'inch'
IE-00413-01	-	IBS086-SMSM-6.0IN	6 +0.20/-0
IE-00413-02	-	IBS086-SMSM-8.0IN	8 +0.20/-0
IE-00413-03	-	IBS086-SMSM-10.0IN	10 +0.20/-0
IE-00413-04	-	IBS086-SMSM-12.0IN	12 +0.24/-0

1.0 Scope

This drawing documents the construction and performance of Instabend 086 cable assemblies manufactured by Times Microwave systems.

2.0 Cable Information

- 2.1 Cable to be INSTABEND 086
- 2.2 Jacket color to be Blue
- 2.3 Jacket material to be FEP
- 2.4 Nominal cable impedance to be 50 ohms
- 2.5 Cable diameter to be 0.108" [2.74mm].

3.0 Connector Information

3.1 Forward Connector

Type SMA (M) Straight Connector (SP110) Connector Body – Stainless Steel, Gold Plated Center Contact – Beryllium Copper, Gold Plated

3.2 After Connector

Type SMA (M) Straight Connector (SP110) Connector Body – Stainless Steel, Gold Plated Center Contact – Beryllium Copper, Gold Plated

Unless otherwise specified, dimensions are in INCH. Tolerances are applicable when specified.	Aŗ	oprova	als			TIMES MICROWAVE SYSTEMS			
	Drawn	YA	10/27/22		II		www.timesmicrowave.com		
These drawings and specifications contain proprietary information	Checked			INSTABEND 086 CABLE ASSEMBLY					
which is the property of	Approved			(Space Assemblies)					
Times Microwave	Approved			Size	CAGE CODE		Drawing No.:		
Systems.				A	6899	99	IE.	-00413-XX	
				Scale:	NA	Rev.	(A)	Sheet: 1 of 3	

	THE REVISION STATUS OF ALL SHEETS OF THIS DRAWING IS THE SAME AS SHEET 1						
REV	DESCRIPTION	DATE	BY				
Α	INITIAL RELEASE	10/27/22	YA				

4.0 Electrical Performance

- 4.1 Frequency range: DC 22GHz
- 4.2 Insertion loss & VSWR: As per below table,

Dwg. Number	Max. Insertion Loss in dB	Max. VSWR
Dwg. Number	@ 22GHz	@ 22GHz
IE-00413-01	1.02	1.35
IE-00413-02	1.24	1.35
IE-00413-03	1.47	1.35
IE-00413-04	1.71	1.35

5.0 Mechanical Performance

- 5.1 Overall Length to be specified length.
- 5.2 Minimum Bend radius is 0.25" [6.35mm].

6.0 Environmental Performance

- 6.1 Installation Temperature Range (-65°C to +125°C)
- 6.2 Storage Temperature Range (-65°C to +125°C)
- 6.3 Operating Temperature Range (-65°C to +125°C)

7.0 Marking

- 7.1 Markers are to be black text on White Color Marker Sleeve.
- 7.2 Marker Configuration to be:

Dwg. Number	Marker 1
IE-00413-01	Times Microwave Systems IBS086-SMSM-6.0IN \$\$\$\$\$
IE-00413-02	Times Microwave Systems IBS086-SMSM-8.0IN \$\$\$\$\$
IE-00413-03	Times Microwave Systems IBS086-SMSM-10.0IN \$\$\$\$\$
IE-00413-04	Times Microwave Systems IBS086-SMSM-12.0IN \$\$\$\$\$

- 7.3 \$\$\$\$\$ = 5-digit Serial Number for this specific configuration.
- 7.4 Register to be Maintained for Serial Number.

Unless otherwise specified, dimensions are in INCH. Tolerances are applicable when spec-	Αŗ	prova	als	_	F	TIMES MICROWAVE SYSTEMS			
ified.	Drawn	YA	10/27/22		www.timesmicrowave.com			crowave.com	
These drawings and specifications contain proprietary information	Checked			INSTABEND 086 CABLE ASSEMBLY (Space Assemblies)					
which is the property of	Approved				blies)				
Times Microwave	Approved			Size CAGE CO		CODE Drawing		No.:	
Systems.				Α	68999		IE-00413-XX		
				Scale:	NA	Rev. ((A)	Sheet: 2 of 3	

	THE REVISION STATUS OF ALL SHEETS OF THIS DRAWING IS THE SAME AS SHEET 1						
REV	DESCRIPTION	DATE	BY				
Α	INITIAL RELEASE	10/27/22	YA				

8.0 NOTES

- 8.1 All Dimensions are in INCH.
- 8.2 Assemblies built in Class 100,000 clean room.
- 8.3 Low outgassing materials per ASTM E595.
- 8.4 Unless Otherwise Specified: Tolerance will be,

Linear Dimension	Tolerance
<20 INCH	±0.4 INCH
20-79 INCH	±0.6 INCH
>79 INCH	±0.8 INCH

^{**}Tolerances are not accumulative.

Unless otherwise specified, dimensions are in INCH. Tolerances are applicable when spec-			_		TIMES	MICROW	/AVE SYSTEMS		
ified.	Drawn	YA	10/27/22		www.timesmicrowave.com			crowave.com	
These drawings and specifications contain proprietary information	Checked			INSTABEND 086 CABLE ASSEMBLY (Space Assemblies)					
which is the property of	Approved				blies)				
Times Microwave	Approved			Size CAGE COI A 68999		CODE Drawing		No.:	
Systems.						99	IE.	-00413-XX	
				Scale:	NA	Rev. ((A)	Sheet: 3 of 3	