

Technical Data Sheet

USB C Hub 4 Port USB 3.1 Gen1 SuperSpeed USB C Upstream

Model Number: CG-4PU31C2P







USB C hub provides 4 USB 3.1 Gen1 ports to include 3 USB-A ports and 1 USB C port. 1 Downstream and 1 upstream port use the reversible USB C connector. USB C hub is a Gen1 hub using USB 3.1 to support Super-Speed 5Gbps data transmission speeds and takes advantage of the reversible type-C port in both directions. This hub is self powered with a 2-pin terminal block connector to supply power input of $+7 \sim 48V$ DC sold separately.

Features

- Compliant with USB 3.1 Gen1 Specifications
- Rigid and Wall and DIN Rail Mountable Metal Case
- Provides 4 (1 USB-C and 3 USB-A) downstream facing USB 3.1 ports (1 USB-C Upstream Port)
- Uses included USB 3.1 C to A cable for upstream data
- Support USB Battery Charging: CDP and DCP modes
- Supports 5Gbps (super-speed), 480Mbps (High-Speed), 12Mbps (Full-Speed), and 1.5Mbps (low-speed) speeds
- Supports 15KV ESD Surge Protection
- Multi Transaction translators (TT) per hub

Product Information

- Model Number: CG-4PU31C2P
- Packing List:
 - o 4 Port USB 3.1 Hub
 - o DIN Rail Mounting Clips and Screws
 - o 3ft. USB 3.0 C to A Cable
 - o Paper Installation Guide
- Optional Accessories: Power adapter is sold separately.



		ns

оресписатоно			
OVERVIEW			
Product Type	USB 3.1 Hub (Backward compatible with USB 2.0/1.1)		
Electrical Protections	Supports 15KV ESD Surge Protection		
Mountable	Wall and DIN Rail Mounting (DIN Rail Clips Included)		
Construction	Metal		
Applications	Data Centers, Automotive peripheral installation, Machine Equipment, Kiosk, Office, and others		
Certs / Compatibility	RoHS, CE, FCC, WEEE		
CONNECTIONS			
Type-A Downstream Ports	4 (3 USB-A ports and 1 USB-C port)		
Type-C Upstream Ports	1 (USB-C)		
7 – 48V Input Power	2-pin terminal block connector		
AVAILABLE POWER MODES			
Mode 1	Bus		
Mode 2	Self power source (+7~48VDC from 2-pin terminal connector)		
ENVIRONMENTAL			
Operating Temperature	0 to 55°C (32 TO 131°F)		
Operating Humidity	5 to 95% RH		
Storage Temperature	-20°C to 85°C (-4 to 185° F)		
DIMENSIONS			
Length	4.50" (11.45 cm)		
Width	2.26" (5.73 cm)		
Height	1.03" (2.63 cm)		
OS SUPPORT			
Windows	Windows 7, Windows 8, Windows 10		
Other	Linux and Mac OS 10.X		
LED			
Power	1(green)		
Downstream Ports	N/A		
WARRANTY			
Warranty Period	1 year from date of purchase		
PRODUCT URL			
CG-4PU31C2P Product Page	https://www.coolgear.com/product/usb-c-hub-4-port-usb-3-1-gen1-superspeed-usb-c-upstream		



© 2017 Coolgear, Inc. All Rights Reserved. All products and accompanying digital documentation including images are the property and / or trademarks of Coolgear Inc. Coolgear Inc. are continuously improving upon its products. Product specifications are subject to change without notice.