


CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	3-1 @20°C	0.650 ohms ±10%
D.C. RESISTANCE	4-5 @20°C	0.125 ohms ±10%
D.C. RESISTANCE	7-9 @20°C	0.035 ohms ±20%
INDUCTANCE	3-1 100kHz, 100mVAC, Ls	700uH ±10%
SATURATION CURRENT	20% rolloff from initial	575mA
LEAKAGE INDUCTANCE	3-1 tie(4+5, 7+9), 100kHz, 100mVAC, Ls	4.5uH typ., 6.5uH max.
DIELECTRIC	3-7 tie(3+4), 4000VAC, 1 second	4000VAC, 1 minute
DIELECTRIC	3-4 625VAC, 1 second	500VAC, 1 minute
URNS RATIO	(3-1):(4-5)	5.50:1, ±1%
URNS RATIO	(3-1):(7-9)	5.50:1, ±1%

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Designed to comply with the following requirements as defined by IEC60950-1, EN60950-1, UL60950-1/CSA60950-1 and AS/NZS60950.1:

- Reinforced insulation for a primary circuit at a working voltage of 400VDC.

Wire insulation & RoHS status not affected by wire color.
Wire insulation color may vary depending on availability.

REV.	DATE	Packaging Specifications Method: Tray PKG-0887 www.we-online.com/midcom		Tolerances unless otherwise specified: Angles: ±1° Fractions: ±1/64 Decimals: ±.005 [.13] Footprint: ±.001 [.03]	DRAWING TITLE TRANSFORMER	PART NO. 7508110329
6B	2/23			This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	eiSos p/n: 7508110329	
6A	11/13	SEE REVISION SHEET FOR REVISION LEVEL				SPECIFICATION SHEET 1 OF 1